

## SeaRox SL 720



## Marine Batts 32

## Comfort Insulation

### Product description

SeaRox SL 720 is a soft, lightweight slab made of stone wool. The product can be supplied with reinforced alu foil.

### Application

SeaRox SL 720 is used for comfort insulation.



### Product Properties


	Performance			Norm
Thermal conductivity	T [°C]	10	50	EN 12667
	$\lambda$ (W/mK)	0,036	0,045	
Nominal density	32 kg/m <sup>3</sup>			EN 1602 / IMO
Compressive strength	-			EN 826
Fire classification	Non-combustible Low Flame-Spread Properties			Acc. IMO FTP code
Water absorption (short term)	< 1 kg/m <sup>2</sup>			EN 1609 AC
Max. Application Temperature	Wool 250°C Facing 80°C			-
Sound absorption directly mounted	$\alpha_w = 0,75$ Thickness: 50 mm			ISO 354 (approximated) Evaluated after ISO 11 654
Facings ( on request)	Reinforced alu foil			IMO A.653(16) (low flame - spread)

### Dimensions

#### SeaRox SL 720

Thickness (mm): 50, 100    Length (mm): 1000    Width (mm): 600

Local variations in standard dimensions might occur.



Rockwool Technical Insulation reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.