


NO: CE-1503/1

1. Unique identification code of the product: **Opti-Step™ 1503**
2. Intended use: **Underlays for laminate floor**
3. Manufacturer: **Sealed Air Svenska AB, Box 146, 578 23 Aneby, Sweden**
4. System of AVCP: **System 4**
5. Harmonized standard: **EN 16354:2018**
6. Notified Body: **N/A**
7. Declared performance:

| Physical Properties | Test Method | Unit | Value | Tolerances |
|---|--------------------------------|--------------------|-----------|------------|
| Nominal Density | ISO 845 | Kg/m ³ | 30 | ± 15% |
| Area Weight (AW) | EN 1923 | gr/m ² | 153 | ± 15% |
| Thickness (t) | EN 823 + A.3.1 | mm | 2 | ± 15% |
| Length (l) | EN 822 + A.3.3 | m | 15-150 | -0%, +5% |
| Width (w) | EN 822 + A.3.3 | mm | 1000-1500 | -1%, +2.5% |
| Compression Strength (CS) | EN826 + A.3.7. | kPa | >20 | - |
| Compressive Creep (CC) | EN 1606 + A.3.8 | kPa | >2 | - |
| Punctual Conformability (PC) | EN 869 + A.3.6 | mm | 1,1 | - |
| Resistance to Impact by Large Diameter Ball (RLB) | EN 13329 | mm | 850 | - |
| Thermal Resistance (R) | EN 12667 | m ² K/W | 0,04 | - |
| Moisture Resistance (SD) | EN 12086, Method A | m | >75 | - |
| Impact Sound Reduction (IS) | EN ISO 10140-3 EN ISO 717-2 | ΔLw in dB | ≥19 | - |
| Emission of Formaldehyde and VOC | EN ISO 16000-9 | | Class A+ | - |
| Alkaline Resistance (AR) | EN 14909 | Pass or Fail | Pass | - |

The performance of the product is in conformity with the declared performance outlined above.
This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


.....
Thomas Piper, Plant Manager

Date: 19.08.19
.....

 Produced in Sweden