

SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-090

Item No: 502016292







Description:

CBS CSK FLAT HD TX30 HALF THRD SST A2 PASSIVATED WAX 6x90

Material: A2

Certificate No.: E-30-20165-16

Report No.: 1015-CPR-30-10720/6

	Nominal diameter	Inner thread diameter	Total length	Head diameter	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre) (N/mm^2)	Head pull-through parameter (N/mm^2)	Yield moment (Nmm)	Tensile capacity (kN)
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)				
										
6x90	5.7 - 6.0	3.6 - 3.85	88.25 - 90.0	11.6 - 12.0	51.75 - 56.25	2.13	17.14 / 13.37	20.17	9353	8.01
Characteristic density of wood ρ_k (kg/m ³)						450	350	400	-	
Durability (i.e. corrosion protection)						Stainless steel A2 (Service Class 3 acc. To EN 1995-1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 18 Apr 2019



Hieu Trong Nguyen