



Stavspiker til generell spikring som: Reisverk, underpanel, utlekting, sløyfer etc.



[NO-DoP-h17/0018](#)

EGENSKAPER



Fordeler:

- Stavspiker 21 grader
- Rundt hode
- Plastbåndet
- Rillet



ANVENDELSE

Bruksområde:

- Tre til tre

TEKNISK DATA

Product dimensions

Art. nr.	Item code	NOBB nr.	Fastener dimensions [mm]					
			d	l	d _h	l _g	t _{fix}	bit
RSN21A42.8X65	75641	55841940	2.8	63.5	6.2	50	42.6	-
RSN21A42.8X75	75642	55841955	2.8	73.5	6.9	53	52.6	-
RSN21A43.1X90	75643	55841966	3.1	88	6.9	70	65.2	-

Product characteristic properties

Art. nr.	Product characteristic properties					
	Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]	Characteristic torsional strength - f _{tor,k} [f _{tor,k}] [Nm]	Torsional ratio
RSN21A42.8X65	3.2	8.9	29.4	3.4	-	-
RSN21A42.8X75	3.2	8.9	29.4	3.4	-	-
RSN21A43.1X90	4.6	8.3	18.1	3.8	-	-

