

LOCK DE-ICER+PTFE

Technical Data Sheet

Creation Date 28/03/2018

Version I

A versatile door lock spray with PTFE. CRC Lock De-Icer quickly de-ices and lubricates all types of locks in one application.

Where to use?

CRC Lock De-Icer can be used with all types of locks.

How does it work?

When applying the CRC Lock De-Icer, it will quickly thaw ice, snow and frost so that locks can be opened again. The PTFE additives provide improved lubrication.

What to expect?

The lock spray will quickly dissolve ice, snow and frost and will inhibit re-freezing. The PTFE will improve lock operation and reduce wear. CRC Lock De-Icer will prevent corrosion of lock parts.

Be prepared

- Before use, carefully read and observe the warning texts on the label
- Always make sure to have a good ventilation.
- Avoid open fire or other sources of ignition in the same room.
- Wash hands after use.
- Dispose empty cans according to your local legislation.

Help for a good application

- Shake before use.
- Push the spray button into the door lock and spray for about 1 second.
- Wait about 30 seconds before opening the lock with the key.
- Repeat if necessary.

Technical data (Aerosol)

Colour: Transparent
 Temperature range: -25°C to 0°C
 Volume: 40 ML



Related products:

- CRC Wipes

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

