

Technical data sheet

domestic Extra
Version 09.2013

Dimensions

| | |
|---------------------------|-----------------------------|
| Tongue and groove | Perfect Fold 3.0 connection |
| Format | Classic Plank |
| Bevels | none |
| Thickness | 8mm |
| Width | 190mm |
| Length | 1200mm |
| Number of panels per pack | 7 |
| m ² per pack | 1,596m ² |
| Heat resistance | 0,06m ² K/W |

Factory warranty

| | Method | Parameters | Norm requirements | Pergo values |
|-------------|-----------------|----------------------------------|-------------------|----------------|
| Usage class | EN 13329 | | | 21-22-23/31-32 |
| CE | EN 14041 | Notified body | 0380-1161 | DOP PL0501 |
| Warranty | Residential use | warranty conditions in each pack | | 20 years |
| | Commercial use | | | 3 years |

General data

| | Method | Parameters | Norm requirements | Pergo values |
|-----------------------|--------------|-----------------------------|-------------------|---------------|
| Wear resistance | EN 13329 | | ≥ 4000 | ≥ 4000 |
| Wear class | EN 13329 | | AC4 | AC4 |
| Impact resistance | EN 13329 | | IC2 | IC2 |
| Scratch resistance | EN 438-2, 25 | | Charge ≥ 3.0 N | Charge ≥ 5 N |
| Slip resistance | EN13893 | | | DS |
| Emission formaldehyde | EN 717 | | | E1 <0,020 ppm |
| Fire classification | EN 14041 | | | Cfl - s1 |
| Moisture swelling | EN 13329 | after 24h immersion at 20°C | ≤18% | ≤ 15% |
| Castor chairs | EN 13329 | Type W(EN 12529) | 25000 cycles | No change |



Technical data sheet

domestic Extra
Version 09.2013

General data

| | Method | Parameters | Norm requirements | Pergo values |
|--------------------------------|---------------------|--------------------------------------|--------------------------|--------------------------|
| General appearance | EN 13329 | Height differences | ≤ 0,15 mm | ≤ 0,10 mm |
| | | Opening between joints | ≤ 0,20 mm | ≤ 0,10 mm |
| | | Cupping in the length | cc ≤ 0,50% cv ≤ 1,00% | cc ≤ 0,50% cv ≤ 1,00% |
| | | Cupping in the width | cc ≤ 0,15% cv ≤ 0,20% | cc ≤ 0,15% cv ≤ 0,20% |
| Light fastness | EN 13329 | Blue reference | Class 6 | Class > 6 |
| Burning cigarette | EN 438-2, 30 | Class 4 | | Class 5 |
| Resistance against staining | EN 13329 | Group 1,2 | Class 5 | Class 5 |
| | | Group 3 | Class 4 | Class 5 |
| | | Group 4 | - | Class 4 |
| Displacement of furniture feet | EN 424 | Foot 0,1 mm / 32 kg | | No change |
| | | Foot 3 mm / 100 kg | | No change |
| | | Foot 2 mm / 100 kg | | No change |
| Dimensional variations | ISO 24339 | Variation in length AND width | | ≤ 0,10% |
| Anti-static | EN 14041 | Charge human body at 25% RH and 23°C | | ≤ 2,0kV |
| Floor heating | On a Pergo underlay | See special instructions | | Suitable |

Ecological certificates

| | |
|-----------------|-----------------|
| U-sign | Request pending |
| AFFSET | A+ |
| Nordic ecolabel | 329 001 |
| PEFC | PEFC/07-32-37 |
| M1 | Request pending |

Note: For all characteristics of the surface layer, a zone of 5mm along the V-groove is excluded

