

Product:

Direct print on a 100 % non-woven substrate

Product description:

These products are screen printed

Product specification:

Length x width
10.05 m x 0.53 m (5.33 m²)

Roll weight
760 g – 1100 g (the total weight varies approx. 5 % depending on the design, structure and quality of the wallpaper)

Substrate/Support Material:

Non- woven 90 g/m² - 110 g/m²

Product composition:

The coating consists of:

- aqueous coating
 - 45-55 % calcium carbonate
 - 25-35 % water
 - 10-20 % polyvinyl ethylene acetate
 - Approx. 5 % titanium dioxide
 - Approx. 5 % additives

Properties non woven:

- RAL- inspected quality
- CE- compliant to EN 15102 : 2007 – A1 : 2011
- Flame-retardant to DIN EN 13501-1
- Water vapour-permeable to DIN 53122
- Highly water resistant
- No expansion/shrinkage
- When hung properly, completely dry strippable later

Industrial standards:

The manufacturing process complies with the RAL stipulations RAL GZ 479 of the “Gütegemeinschaft Tapete” (“Quality Association for Wallpaper”) and the following European industrial standards:

EN 233
Specification for finished paper, vinyl and plastics wallcoverings

EN 235
Wallcoverings- Vocabulary and symbols

EN 12149
Determination of migration of heavy metals and certain other elements, of vinyl chloride monomer and of formaldehyde release

EN 12956
Determination of dimensions, straightness, spongeability and washability



CE	
0764	0765
Tapetenfabrik Güter Rasch GmbH & Co. KG	
Raschplatz 1 D-49565 Bramsche	
2014	
LE 03	
EN 15102 : 2007 – A1 : 2011	
Decorative wallcovering	
Reaction to fire class B-s1, d0	
Release of formaldehyde (P _{form})	
Release of heavy metals and specific elements	
Sb < 0.05 mg/kg As < 0.05 mg/kg Ba < 1 mg/kg	
Cd < 0.05 mg/kg Cr < 0.7 mg/kg Pb < 0.7 mg/kg	
Hg < 0.05 mg/kg Se < 0.05 mg/kg	
Release of vinyl chloride monomer (VCM)	

Manufacturer:

Kupferoth Interiors GmbH & Co KG
Raschplatz 1
49565 Bramsche
Tel. +49 / 5461 / 81 10
Fax +49 / 5461 / 81 1157