

ENVIRONMENTAL PRODUCT DECLARATION

ISO 14025 ISO 21930 EN 15804

**epd-norge.no**
The Norwegian EPD Foundation

Owner of the declaration	Saint-Gobain Byggevarer as
Program holder	The Norwegian EPD Foundation
Declaration number	NEPD00279E
Issue date	20.10.2014
Valid to	20.10.2019

Leca Lettveggsblokk 88 mm, Lightweight Concrete Block

Product

Saint-Gobain Byggevarer as

Owner of the declaration



General information

Product:

Leca Lettvegsblokk 88 mm, Lightweight Concrete Block

Program holder:

The Norwegian EPD Foundation
 P.O.Box 5250 Majorstuen
 0303 Oslo
 Phone: +47 23 08 80 00
 e-mail: post@epd-norge.no

Declaration number:
This declaration is based on Product Category Rules:

EN 15804:2012+A1:2013 serve as core PCR
 Requirements on the EPD for Lightweight concrete.

Declared unit:

1 m3 Leca Lettvegsblokk 88 mm, Lightweight Concrete Block

Declared unit with option:

A1,A2,A3,A4

Functional unit:
The EPD has been worked out by:

The declaration has been developed using EPDGen-version 1.0, Approval: NEPDT02
 Company specific data are collected and registry by:
Stian Gravnås
 Company specific data are audited by:
Line Holaker

Verification:

Independent verification of data, other environmental information and EPD has been carried out in accordance with ISO14025, 8.1.3 and 8.1.4

externally



Senior Researcher Anne Rønning
 (Independent verifier approved by EPD-Norway)

Declared unit:

1 m3 Leca Lettvegsblokk 88 mm, Lightweight Concrete Block

Key environmental indicators	Unit	Cradle to gate A1 - A3	Transport A4
Global warming	kg CO2 eqv	118,15	3,69
Energy use	MJ	1569,2545	48,2833
Dangerous substances		*	*

*The product contains no substances from the REACH Candidate list or the Norwegian priority list

Owner of the declaration:

Saint-Gobain Byggevarer as
 Contact person: Line Holaker
 Phone: +47 22 88 77 00
 e-mail: [info\(at\)weber-norge.no](mailto:info(at)weber-norge.no)

Manufacturer:

Saint-Gobain Byggevarer as

Place of production:

Weber Leca Borge, Moumgt.,
 1658 Torp, Norway

Management system:

ISO 9001, ISO 14001

Org. No:


940 198 178

Issue date:
Valid to:
Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

Year of study:

2014

Approved:


Dagfinn Malnes
 Managing Director of EPD-Norway

Product

Product description:

Leca Lettvegsblokk 88 mm is produced by Leca lightweight aggregate, cement, sand and water. Leca Lettvegg is a fast and efficient solution for non-bearing interior walls.

Technical data:

See www.weber-norge.no

Reference service life:

As for the building

Product specification:

The composition of the product is described in the following table:

Materials	Percent
Cement	11,83
Aggregate	76,14
Water	9,96
Packaging	2,07

Market:

Norway

LCA: Calculation rules

Declared unit:

1 m³ Leca Lettvegsblokk 88 mm, Lightweight Concrete Block

Cut-off criteria:

All major raw materials and all the essential energy is included. The production process for raw materials and energy flows that are included with very small amounts (<1%) are not included.

Allocation:

The allocation is made in accordance with provisions in EN 15804. Incoming energy and water, and in-house waste from the production, is allocated equally among all products through mass allocation. Effects of primary production of recycled materials are allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:

Materials	Data quality	Source	Year
Aggregate	EPD	NEPD00120E	2013
Aggregate	EPD	NEPD00120E	2013
Aggregate	Database	Østfoldforskning	2012
Cement	EPD	NEPD00024N	2013
Packaging			
Water			
Packaging	European Average	APME	

System boundary:

All processes from raw material extraction to product from the factory gate are included in the analysis (A1-A3). In addition, transportation to a central warehouse placed in accordance with guidelines issued by the EPD Norway (A4) is included.

FlowChart:



LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production site to user (A4)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck	75 %	Lorry to market	50	0,015594	l/tkm	0,78
Railway
Boat
Other

Installation in the building (A5)

.	Unit	Value
Auxiliary	kg	0
Water consumption	m ³	0
Electricity consumption	kWh	0
Other energy carriers	MJ	0
Material loss	kg	0
Output materials from waste treatment	kg	0
Dust in the air	kg	0

Label

Maintenance (B2)/Repair (B3)

.	Unit	Value
Maintenance cycle	.	0
Auxiliary	kg	0
Other resources	kg	0
Water consumption	M ³	0
Electricity consumption	kWh	0
Other energy carriers	MJ	0
Material loss	kg	0

Use (B1):

.	Unit	Value
No effect	0	0

End of Life (C1, C3, C4)

.	Unit	Value
Hazardous waste disposed	kg	0
Collected as mixed construction waste	kg	0
Reuse	kg	0
Recycling	kg	0
Energy recovery	kg	0
To landfill	kg	0

Transport to waste processing (C2)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck	0 %	.	0	0	l/tkm	0
Railway
Boat
Other

Benefits and loads beyond the system boundaries (D)

LCA: Results

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage				Construction installation stage	User stage								End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Construction/ Installation stage	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction/ demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	

Environmental impact

Parameter	Unit	A1	A2	A3	A4	A5	C1	C2
GWP	kg CO ₂ -eqv	1,02E+002	3,05E+000	1,31E+001	3,69E+000			
ODP	kg CFC11 -eqv	1,18E-006	0,00E+000	1,97E-006	0,00E+000			
POCP	kg C ₂ H ₄ -eqv	1,19E-001	3,23E-003	3,15E-002	9,75E-003			
AP	kg SO ₂ -eqv	3,05E-001	1,02E-002	5,13E-003	2,25E-003			
EP	kg PO ₄ ³⁻ -eqv	3,04E-002	1,54E-003	2,65E-003	1,50E-003			
ADPM	kg Sb -eqv	1,45E-004	0,00E+000	5,16E-005	0,00E+000			
ADPE	MJ	5,68E+002	4,03E+001	1,68E+002	4,84E+001			

GWP Global warming potential; **ODP** Depletion potential of the stratospheric ozone layer; **POCP** Formation potential of tropospheric photochemical oxidants; **AP** Acidification potential of land and water; **EP** Eutrophication potential; **ADPM** Abiotic depletion potential for non fossil resources; **ADPE** Abiotic depletion potential for fossil resources

Resource use

Parameter	Unit	A1	A2	A3	A4	A5	C1	C2
RPEE	MJ	2,80E+002	5,45E-002	1,07E+002	8,33E-002			
RPEM	MJ	2,17E-001	1,88E-002	1,43E-001	0,00E+000			
TRPE	MJ	2,81E+002	7,33E-002	1,08E+002	8,33E-002			
NRPEE	MJ	6,58E+002	4,02E+001	1,78E+002	4,82E+001			
NRPEM	MJ	0,00E+000	0,00E+000	0,00E+000	0,00E+000			
TNRPE	MJ	6,58E+002	4,02E+001	1,78E+002	4,82E+001			
SM	kg	1,81E+001	0,00E+000	0,00E+000	0,00E+000			
RSF	MJ	0,00E+000	0,00E+000	0,00E+000	0,00E+000			
NRSF	MJ	3,06E+002	0,00E+000	0,00E+000	0,00E+000			
W	m ³	1,27E+002	3,76E-001	2,44E+001	4,31E-001			

RPEE Renewable primary energy resources used as energy carrier; **RPEM** Renewable primary energy resources used as raw materials; **TRPE** Total use of renewable primary energy resources; **NRPEE** Non renewable primary energy resources used as energy carrier; **NRPEM** Non renewable primary energy resources used as materials; **TNRPE** Total use of virgin, non-renewable resources with energy content; **SM** Use of secondary materials; **RSF** Use of renewable secondary fuels; **NRSF** Use of non renewable secondary fuels; **W** Use of net fresh water

End of life - Waste

Parameter	Unit	A1	A2	A3	A4	A5	C1	C2
HW	kg	3,95E-003	0,00E+000	2,22E-002	0,00E+000			
NHW	kg	1,58E+001	8,66E-003	2,20E+000	9,00E-003			
RW	kg	0,00E+000	0,00E+000	0,00E+000	0,00E+000			

HW Hazardous waste disposed; **NHW** Non hazardous waste disposed, **RW** Radioactive waste disposed

End of life - Output flow

Parameter	Unit	A1	A2	A3	A4	A5	C1	C2
CR	kg	0,00E+000	0,00E+000	2,00E-003	0,00E+000			
MR	kg	5,80E-002	0,00E+000	4,22E-001	0,00E+000			
MER	kg	0,00E+000	0,00E+000	0,00E+000	0,00E+000			
EEE	MJ	0,00E+000	0,00E+000	0,00E+000	0,00E+000			
ETE	MJ	0,00E+000	0,00E+000	0,00E+000	0,00E+000			

CR Components for reuse; **MR** Materials for recycling; **MER** Materials for energy recovery; **EEE** Exported electric energy; **ETE** Exported thermal energy

Additional Norwegian requirements

Electricity

The following data from ecoinvent v3 (June 2012) for Norwegian production mix included import, low voltage is used; Energy/Electricity country mix/Low voltage/Market: Electricity, low voltage {NO}| market for | Alloc Def, U. Production of transmission lines, in addition to direct emissions and loss in grid are included. Characterisation factors stated in EN 15804:2012+A1:2013 are used. This gives following greenhouse gas emissions: 24 g CO₂-eqv/kWh

Hazardous substances

None of the following substances have been added to the product: Substances on the REACH Candidate list of substances of very high concern (checked 10.10.2014) substances on the Norwegian Priority list (checked 10.10.2014) and substances that lead to the product being classified as hazardous waste. The chemical content of the product complies with regulatory levels as given in the Norwegian Product Regulations

Indoor air

The product meets the requirements for low pollutant (M1) by EN15251:2007 Appendix E. The product has no impact on the indoor environment.

Bibliography




NS-EN ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures

NS-EN ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines

NS-EN 15804:2012+A1:2013 Sustainability of construction works - Environmental product declaration - Core rules for the product category of construction products

ISO 21930:2007 Sustainability in building construction - Environmental declaration of building products

www.bau-umwelt.com: Requirements on the EPD for Light weight concrete Vold, M and Edvardsen, T, 2013: Weber EPD Generator Background information, Østfoldforskning AS, Fredrikstad, Norge, Nov 2013

 epd-norge.no The Norwegian EPD Foundation	Program holder and publisher The Norwegian EPD Foundation P.O.Box 5250 Majorstuen 0303 Oslo Norway	Phone: +47 23 08 80 00 email: post@epd-norge.no web: www.epd-norge.no
	Owner of the declaration Saint-Gobain Byggevarer as P.O. Box 216 Alnabru 0614 Oslo, Norway	Phone: +47 22 88 77 00 Fax: +47 22 64 54 54 email: info(at)weber-norge.no web: www.weber-norge.no
	Author of the Life Cycle Assessment Østfoldforskning AS Stadion 4 1671 Kråkerøy, Norway	Phone: +47 69 35 11 00 Fax: +47 69 34 24 94 email: post@ostfoldforskning.no web: www.ostfoldforskning.no