

Technical data

Reaction to fire	EN 13501-1	B -s1 (Hardly flammable)
Formaldehyde emission	EN 717-1	E1 (< 0,05ppm)
Brinell hardness	EN 1534	80N /mm ²
Thermal resistance	EN 12664	R < 0.10 (m ² x K)/W
Due to the nature of the material this table shows typical values.		

Installation

Installation method	Floating installation, Välinge 2G/5G®
Installation instruction	Download from www.bjelin.com/installation
Under floor heating compatible	Maximal floor surface temperature 27°C
Underlayment material	Foam with CS ≥ 60 kPa & CC ≥ 5 kPa

Size and package

	2379 x 223 x 11mm	2379 x 283 x 11mm
Length (mm)	2379	2379
Width (mm)	223	283
Thickness (mm)	11	11
Wear layer thickness (mm)	0,6	0,6
Boards / box	4	3
m ² / box	2,12	2,02
m ² / full pallet	101,76	96,96
Weight / m ² (kg)	10	10
Weight / box (kg)	21,2	20,2
Weight / full pallet (kg)	1017,60	1063,68

Maintenance

Care & Maintenance products	- Osmo Opti-set - Osmo Wash & Care - Osmo Liqued wax cleaner - Osmo Polyx®-oil
-----------------------------	--