



BASIC COMFORT

FS2025

BERKUT 5 - FULL BODY HARNESS

FS2025 BERKUT 5 is a full body harness with a dorsal D-Ring (A - EN361) and 2 front loops (1/2 A + 1/2 A - EN361). This harness is built in two colors (high visibility orange and black) for easier orientation when dressing and it has comfort paddings at shoulders and legs. It has 5 adjustment points at shoulders and chest and legs, which make it perfectly adjustable to the user. The grey contrasting stitch on the webbing allows the inspection to be easier. This harness is identified with S/N tag and QR code for easy tracking and control.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN361:2002
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Steel
TEXTILE PARTS	Polyester
OTHER COMPONENTS MATERIAL	Silicone, PA6
WEBBING TYPE	PES webbing 45mm high visibility; PES elastic webbing 45mm black
D-RINGS	ST D-ring at back, 2 front loops
ANCHOR POINTS (A)	2
SHOULDER PADDING	Yes
LEG PADDING	Yes
SEAT CONNECTION POINT	No
TOOL HOLDERS	No
ADJUSTMENT POINTS	5
BUCKLES	1 ST deluxe buckles; 2 ST bar buckles
FALL ARREST INDICATORS	Yes
LANYARD KEEPERS	No
WEIGHT PER SIZE EAN PER SIZE	FS2025-S/M - 1.90kg - 5605423270877 FS2025-L/XL - 2.10kg - 5605423470390 FS2025-XXL - 2.30kg - 5605423270860



BASIC COMFORT

FS2025

BERKUT 5 - FULL BODY HARNESS

FS2025 BERKUT 5 é um arnês de corpo inteiro com um D-Ring dorsal (A - EN361) e 2 loops frontais (1/2 A + 1/2 A - EN361). Este arnês é construído em duas cores (laranja de alta visibilidade e preto) para facilitar a orientação ao vestir e possui padding confortável nos ombros e pernas. Possui 5 pontos de ajuste nos ombros, peito e pernas, que o tornam perfeitamente ajustável ao utilizador. A costura cinzenta que contrasta com as fitas permite uma inspeção mais fácil. Este arnês é identificado com etiqueta S/N e código QR para fácil rastreabilidade e controlo.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN361:2002
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Steel
COMPONENTES TÊXTEIS	Polyester
OUTROS MATERIAIS	Silicone, PA6
TIPO DE FITA	PES webbing 45mm high visibility; PES elastic webbing 45mm black
D-RINGS	ST D-ring at back, 2 front loops
PONTOS DE ANCORAGEM (A)	2
PADDING OMBROS	Yes
PADDING PERNA	Yes
PONTO LIGAÇÃO DE CADEIRA	No
SUPORTE DE FERRAMENTAS	No
PONTOS DE AJUSTE	5
FIVELAS	1 ST deluxe buckles; 2 ST bar buckles
INDICADORES DE QUEDA	Yes
SUPORTE DE LONGES	No
PESO POR TAMANHO EAN POR TAMANHO	FS2025-S/M - 1.90kg - 5605423270877 FS2025-L/XL - 2.10kg - 5605423470390 FS2025-XXL - 2.30kg - 5605423270860



PROFESSIONAL

FS800-SP2

SAFESTEP DUO - SUSPENSION TRAUMA RELIEF STRAP

FS800-SP2 is a foot loop designed to avoid hang trauma after a fall.

- Allows to place both feet on the loop;
- Easy to use and fits all leg lengths;
- Silicone bag assures safe accommodation of the equipment and, due to being water resistant, this silicone innovation has the advantage of ensuring greater protection of the webbing and, consequently, longer durability of the equipment;
- The bags can significantly accelerate the unwinding or reeling of the webbing and its quick opening or closing by means of a semi-automatic zipper.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	N/A
INSPECTION	N/A
TRACEABILITY	S/N QR Code
STANDARDS	N/A
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Polyester
WEIGHT PER SIZE EAN PER SIZE	FS800-SP2 - 1.76kg - 5605423802290



PROFESSIONAL

FS800-SP2

SAFESTEP DUO - SUSPENSION TRAUMA RELIEF STRAP

FS800-SP2 é um pedal projetado para evitar traumas após uma queda.

- Permite colocar ambos os pés no loop;
- Fácil de usar e adapta-se a todos os comprimentos de perna;
- Bolsa de silicone garante acomodação segura do equipamento e, por ser resistente à água, essa inovação do silicone tem a vantagem de garantir maior proteção da cinta e, conseqüentemente, maior durabilidade do equipamento;
- Os sacos podem acelerar significativamente o desenrolamento ou enrolamento do tecido e sua rápida abertura ou fechamento por meio de um zíper semiautomático.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	N/A
INSPEÇÃO	N/A
RASTREABILIDADE	S/N QR Code
NORMAS	N/A
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL

Polyester

PESO POR TAMANHO | EAN POR TAMANHO

FS800-SP2 - 1.76kg - 5605423802290



BASIC

FS516-LN

CHIMANGO 2 - Y LANYARD WITH ENERGY ABSORBER

FS516 CHIMANGO 2 is a double lanyard that physically links the user to the workplace structure and arrests the free fall of the user (EN354, EN355) . It is made with 27mm polyester webbing, a PES 45mm energy absorber, PES heavy duty seams, and support maximum load of 140 kg.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PES, Polimero, Steel, Silicone
WEBBING TYPE	PES webbing 27 mm x 3 mm
ROPE TYPE	PES webbing 27mm
CONNECTORS	FS802 screw lock 25kN; FS843 auto lock 25kN (other combinations on request)
MAX LENGTH	2m
ENERGY ABSORBER	Yes, PES - up to 120 Kg
SEAMS PROTECTOR	No
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN PER SIZE	FS516-LN-1M - 1.06kg - 5605423700855 FS516-LN-1.5M - 1.59kg - 5605423700763 FS516-LN-2M - 1.90kg - 5605423700961



BASIC

FS516-LN

CHIMANGO 2 - Y LANYARD WITH ENERGY ABSORBER

FS516 CHIMANGO 2 é uma longe dupla que liga fisicamente o utilizador à estrutura do local de trabalho e impede a queda livre do utilizador (EN354, EN355) . É feito com fita de poliéster de 27 mm, absorvedor de energia PES de 45 mm, costuras de poliéster e suporta carga máxima de 140 kg.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PES, Polimero, Steel, Silicone
TIPO DE FITA	PES webbing 27 mm x 3 mm
TIPO DE CORDA	PES webbing 27mm
CONECTORES	FS802 screw lock 25kN; FS843 auto lock 25kN (other combinations on request)
COMPRIMENTO MÁX	2m
ABSORBEDOR DE ENERGIA	Yes, PES - up to 120 Kg
PROTETOR DE COSTURAS	No
TESTADO ARESTAS CORTANTES	No
PESO POR TAMANHO EAN POR TAMANHO	FS516-LN-1M - 1.06kg - 5605423700855 FS516-LN-1.5M - 1.59kg - 5605423700763 FS516-LN-2M - 1.90kg - 5605423700961