



Leica Lino

One of the industry's most versatile and precise line and point lasers that can adapt to any scenario

Our unique technologies

Technology from Leica Geosystems



Outstanding visibility

All Leica Lino products incorporate decades of knowledge and experience in the fields of optics and electronics. The results are outstanding visibility and high accuracy of our red and green lasers.

Li-Ion

Li-ion batteries can run a Lino for up to 44 hours on a single charge (depending on the model). In addition, the Lino tri-power concept offers run/charge capability along with an alkaline battery backup tray to keep you going.



Ruggedness

Leica Lino products are well crafted with high quality materials, therefore perfectly suited for construction sites. Each product is fully tested to meet Leica Geosystems quality standards.

Magnetic adapters

The Leica Lino products can easily be connected to precision engineered adapters via strong magnets, allowing you to easily position it for any possible measuring scenario.



Lino L2P5

Multi Line & Point Layout Tool



[EXPLORE >](#)

Lino L2P5 combines advantages of both line and point lasers. The cross lines support alignment tasks and the five points allow you to plumb, set out or transfer measured points. Leica optics extend your working range significantly

- Self-Leveling
- Range: 82' with receiver 262'
- Visibility: up to 2 times better than DIY line lasers

[LEARN MORE >](#)



Reliable, Quick Layouts

Easy to setup: self-leveling, quick to plumb, sharp, bright, visible lines



Works For all Applications

Drywall, partitions, ceilings, flooring and millwork with a full line of accessories



Cost Effective Solutions

Included Li-Ion battery works for 44 hrs, saving \$360/yr in disposable batteries

Replaceable glass lens saves buying a replacement unit saving \$300

Pro-Kit

- Lino L2P5 Laser Layout Tool
- Molded Case
- Twist 360
- Target Plate
- Li-Ion Battery / Charger
- AA Battery Tray



Technical Data

Accuracy, Typical	±0.08" @ 33'
Range	82'
Range w/ Receiver	262'
Laser Type	Class 2 635nm
Laser Power Output	30mW
Visibility	0.2 Spectral Efficiency
Leveling System	Automatic Pendulum Lockable
Tripod Thread	1/4", 5/8"
Battery Runtime	Up to 44 hrs of operation
Batteries	3.6V/18.7Wh Li-Ion included or type AA, 3 x 1.5 V
Protection Class	IP54
Dimensions	2.5 x 3.9 x 4.3 in

[See Full Specs >](#)

Layout Accessories

- DISTO D2
- DISTO E7500i
- DISTO S910
- DISTO Plan

[View Video Here >](#)

Lino Adapters

- Twist 360
- Twist 250
- Clamp 290
- Receiver RGR 200
- Wall Mount UAL 130

[View Video Here >](#)

[Laser Level Basics >](#)

[Lino FAQs >](#)



Our dedication to quality assures that the products we deliver are of best quality. And with extensive lab testing, you can rest assured that your device is of highest durability.