



DELUXE SERIES



STRAIGHT-FORWARD POWER AND PERFORMANCE.

Clear snow without question or compromise. Easy manoeuvring and control with Auto-Turn steering, standard on all Deluxe Sno-Thros. With several engine choices and machine width's, there's a reason it's one of our best sellers. The Deluxe Series is available with EFI (electronic fuel injection). These engines deliver all the power you need with less maintenance, increased fuel efficiency and easy one-pull starting. Our exclusive Dual-Belt Drive system provides unmatched power and increased belt life while our Super High Output Impeller (SHO) technology will breeze through those heavy, wet storms with ease.

90 DAY
LTD. COMMERCIAL
WARRANTY

3 YEAR
LTD. RESIDENTIAL
WARRANTY

AUTO-TURN™ STEERING

Effortless, zero-degree turning radius.

AUGER

Our steel serrated 35.6 cm (14") auger delivers exceptional performance through all types of snow conditions.

HEADLIGHT

The King of Snow shines brighter than ever with its new LED dash light.

TYRES

41cm (16") directional tyres provide improved mobility and agility.

THROWING PERFORMANCE

Throw snow ranging from 0.9-15.2 m (3-50 ft) to allow for maximum precision.

ENGINE

Choose from two different Ariens AX engines.

PRODUCT SPECIFICATIONS

RAPIDTRAK

DESIGNATION	DELUXE 24	DELUXE 28	DELUXE 28RT
MODEL #	921323	921324	921330
STAGE TYPE	TWO STAGE	TWO STAGE	TWO STAGE
ENGINE POWER	254CC (16.9NM)	291CC (19.5NM)	291CC (19.5NM)
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX
STARTING SYSTEM	230V/RECOIL	230V/RECOIL	230V/RECOIL
CLEARING WIDTH	24 IN (60.1 CM)	28 IN (71.2 CM)	28 IN (71.2 CM)
HOUSING HEIGHT	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)
THROWING DISTANCE	0.9 - 15.2 M	0.9 - 15.2 M	0.9 - 16.7 M
CHUTE TURNING RADIUS	200°	200°	200°
CHUTE ROTATION	2.5X ICE DRILL	2.5X ICE DRILL	2.5X ICE DRILL
DEFLECTOR CONTROL	REMOTE	REMOTE	REMOTE
TYRE SIZE	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	5.5 IN (14 CM) WIDE TRACK
TYRE TYPE	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TRACK
STEERING	AUTO-TURN	AUTO-TURN	AUTO-TURN
DRIVE TYPE	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC
SPEEDS	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE
GEAR CASE	CAST IRON	CAST IRON	CAST IRON
GEAR CASE WARRANTY	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER TYPE	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED
SKID SHOES	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE
SCRAPER BAR	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM
LENGTH	58.3 IN (148.1 CM)	58.3 IN (148.1 CM)	58.5 IN (148.6 CM)
WIDTH	26.4 IN (67.1 CM)	29.9 IN (75.9 CM)	29.9 IN (75.9 CM)
HEIGHT	45.9 IN (116.6 CM)	45.9 IN (116.6 CM)	45.9 IN (116.6 CM)
WEIGHT	238.1 LBS (108 KG)	259 LBS (117.5 KG)	283.1 LBS (128.4 KG)
ACCESSORIES AT A GLANCE	HANDWARMER KIT, TYRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	HANDWARMER KIT, TYRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	HANDWARMER KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER

Registered trademark and ™ trademark of AriensCo. Kawasaki®, Kohler® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2022 AriensCo. All rights reserved.

VISIT [ARIENS.EU](https://www.ariens.eu) FOR DETAILS

AN **ARIENS|CO** BRAND