



ETA-Danmark A/S  
Göteborg Plads 1  
DK-2150 Nordhavn  
Tel. +45 72 24 59 00  
Fax +45 72 24 59 04  
Internet [www.etadanmark.dk](http://www.etadanmark.dk)

Authorised and notified according  
to Article 29 of the Regulation (EU)  
No 305/2011 of the European  
Parliament and of the Council of 9  
March 2011

MEMBER OF EOTA



## European Technical Assessment ETA-07/0212 of 30/08/2015

### I General Part

**Technical Assessment Body issuing the ETA and designated according to Article 29 of the Regulation (EU) No 305/2011: ETA-Danmark A/S**

**Trade name of the construction product:**

SIMA Angle Brackets type V1, V1Ø7, V2, V2PL, V2 Stainless, V2Ø7, V3, V4, V4PL, V4 Stainless, V6, V7, V7PL, V8, V10 2,5, V10, V12, V13, V14, V15, V20, V21, V26, V27, V170, LV1, P4, P1-8, P1-10, P1-12, P2-10, P2-12, 1-150, K4

**Product family to which the above construction product belongs:**

Three-dimensional nailing plate (timber-to-timber/timber-to-concrete angle bracket)

**Manufacturer:**

Sima Industri ApS  
Industrivej Nord 40  
DK-7490 Aulum  
Tel. +45 97 47 26 11  
Fax +45 97 47 37 11  
Internet [www.simaindustri.dk](http://www.simaindustri.dk)

**Manufacturing plant:**

Sima Industri ApS  
Industrivej Nord 40  
DK-7490 Aulum

**This European Technical Assessment contains:**

54 pages including 3 annexes which form an integral part of the document

**This European Technical Assessment is issued in accordance with Regulation (EU) No 305/2011, on the basis of:**

Guideline for European Technical Approval (ETAG) No. 015 Three Dimensional Nailing Plates, April 2013, used as European Assessment Document (EAD).

**This version replaces:**

The previous ETA with the same number issued on 2013-06-26 and expiry on 2015-09-07

Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and should be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full (excepted the confidential Annex(es) referred to above). However, partial reproduction may be made, with the written consent of the issuing Technical Assessment Body. Any partial reproduction has to be identified as such.

## II SPECIFIC PART OF THE EUROPEAN TECHNICAL ASSESSMENT

### 1 Technical description of product and intended use

#### Technical description of the product

SIMA Angle Brackets type V1, V1Ø7, V2, V2PL, V2 Stainless, V2Ø7, V3, V4, V4PL, V4 Stainless, V6, V7, V7PL, V8, V10 2,5, V10, V12, V13, V14, V15, V20, V21, V26, V27, V170, LV1, P4, P1-8, P1-10, P1-12, P2-10, P2-12, 1-150 and K4 are one piece, non-welded angle brackets. They are intended for timber-to-timber, timber-to-concrete or timber-to-steel connections fastened by a range of nails or bolts.

Most of the angle brackets are made from pre-galvanized steel Grade S250GD + min. Z275 according to EN 10346.

The angle brackets V2 Stainless and V4 Stainless are made from stainless steel 1.4301, 1.4401, 1.4404, 1.4541 or 1.4571 according to EN 10088-2 with a minimum characteristic yield stress of 235 MPa and a minimum ultimate tensile strength of 330 MPa. Dimensions, hole positions and typical installations are shown in Annex B.

Angle bracket 1-150 are made from steel Grade S235JRG2 according to EN 10025-2 with a corrosion protection of hot dipped galvanized according to EN ISO 1461 with a zinc coating thickness of approximately 55 µm. Additionally all angle brackets can also be made using these specifications.

Additionally, the angle brackets type V2PL can be made from 1,5 mm pre-galvanized steel in grades from Grade S350GD to Grade S500GD + min. Z275 according to EN 10346 and bracket type V4PL can be made from 2,0 mm pre-galvanized steel in grades from Grade S350GD to Grade S500GD + min. Z275 according to EN 10346.

### 2 Specification of the intended use in accordance with the applicable EAD

The angle brackets are intended for use in making connections in load bearing structures, as a connection between two timber beams or a timber beam and a timber column or between a timber member and a concrete or steel member, where requirements for mechanical resistance and stability and safety in use in the sense of the Basic Works Requirements 1 and 4 of Regulation (EU) 305/2011 shall be fulfilled.

The connection may be with a single angle bracket or

with an angle bracket on each side of the fastened timber member.

The static and kinematic behaviour of the timber members or the supports shall be as described in Annex C.

The wood members can be of solid timber, glued laminated timber and similar glued members, or wood-based structural members with a characteristic density from 290 kg/m<sup>3</sup> to 420 kg/m<sup>3</sup>.

This requirement to the material of the wood members can be fulfilled by using the following materials:

- Solid timber classified to C14-C40 according to EN 338 / EN 14081
- Glued members of timber classified to C14-C40 according to EN 338 / EN 14081 when structural adhesives are used.
- Glued laminated timber classified to GL24c or better according to EN 1194 / EN 14080.
- Solid Wood Panels, SWP according to EN 13353.
- Laminated Veneer Lumber LVL according to EN 14374
- Laminated Strand Lumber, e.g. Parallam and Timber Strand
- Plywood according to EN 636
- Oriented Strand Board, OSB according to EN 300

Annex C states the load-carrying capacities of the Angle Bracket connections for a characteristic density of 350 kg/m<sup>3</sup>.

For timber or wood based material with a lower characteristic density than 350 kg/m<sup>3</sup> the load-carrying capacities shall be reduced by the  $k_{dens}$  factor:

$$k_{dens} = \left( \frac{\rho_k}{350} \right)^2$$

Where  $\rho_k$  is the characteristic density of the timber in kg/m<sup>3</sup>.

The design of the connections shall be in accordance with Eurocode 5 or a similar national Timber Code. The wood members shall have a thickness which is larger than the penetration depth of the nails into the members.

The angle brackets may also be used for connections between a timber member and a member of concrete, steel or masonry.

The Angle brackets are primarily for use in timber structures subject to the dry, internal conditions defined by service class 1 and 2 of Eurocode 5, and for connections subject to static or quasi-static loading.

The angle brackets can also be used in outdoor timber

structures, service class 3, when a corrosion protection in accordance with Eurocode 5 is applied, or when stainless steel with similar or better characteristic yield and ultimate strength is employed.

The scope of the brackets regarding resistance to corrosion shall be defined according to national provisions that apply at the installation site considering environmental conditions.

The provisions made in this European Technical Assessment are based on an assumed intended working life of the connectors of 50 years.

The indications given on the working life cannot be interpreted as a guarantee given by the producer or Assessment Body, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

### 3 Performance of the product and references to the methods used for its assessment

Characteristic	Assessment of characteristic
<b>3.1 Mechanical resistance and stability*) (BWR1)</b>	
Characteristic load-carrying capacity	See Annex C
Stiffness	No performance determined
Ductility in cyclic testing	No performance determined
<b>3.2 Safety in case of fire (BWR2)</b>	
Reaction to fire	The angle brackets are made from steel classified as Euroclass A1 in accordance with EN 1350-1 and EC decision 96/603/EC, amended by EC Decision 2000/605/EC
<b>3.3 Hygiene, health and the environment (BWR3)</b>	
Influence on air quality	The product does not contain/release dangerous substances specified in TR 034, dated March 2012 0**)
<b>3.7 Sustainable use of natural resources (BWR7)</b>	
	No Performance Determined
<b>3.8 General aspects related to the performance of the product</b>	
	The angle brackets have been assessed as having satisfactory durability and serviceability when used in timber structures using the timber species described in Eurocode 5 and subject to the conditions defined by service class 1, 2 and 3
Identification	See Annex B

\*) See additional information in section 3.8 – 3.9.

\*\*) In addition to the specific clauses relating to dangerous substances contained in this European technical Assessment, there may be other requirements applicable to the products falling within its scope (e.g. transposed European legislation and national laws, regulations and administrative provisions). In order to meet the provisions of the Construction Products Regulation, these requirements need also to be complied with, when and where they apply.

### 3.9 Methods of verification

The characteristic load-carrying capacities have been calculated without considering different ratios between the partial factors for timber connections and steel cross sections. Therefore, in the end use calculation based on this ETA, this shall be considered.

The values in annex C have been determined by multiplying the calculated resistance of the connection by  $k_{mod}$  to consider load duration and service classes in accordance with EC 5.

### 3.10 Mechanical resistance and stability

See annex C for characteristic load-carrying capacity in the different directions  $F_1$  to  $F_5$ .

The characteristic capacities of the angle brackets are determined by calculation assisted by testing as described in the EOTA Guideline 015 clause 5.1.2. They should be used for designs in accordance with Eurocode 5 or a similar national Timber Code.

#### *Connector nails in accordance to ETA-09/0273*

The load bearing capacities of the brackets have been determined based on the use of Paslode Connector nails 4,0 x 40 mm and 4,0 x 60 mm in accordance with the ETA-09/0273 for the nails. The fastener can be replaced by fastener mentioned in the ETA-09/0273 with the same or higher performance. The capacity of the connection may not be higher than the load mentioned in this ETA.

The capacity of the nails used in calculation are:

$$F_{ax,Rk} = 1,027 \text{ kN}$$
$$F_{v,Rk} = 1,877 \text{ kN}$$

Calculations made before 2015 are based on the following nail values from an older version of ETA-09/0273:

$$F_{ax,Rk} = 0,998 \text{ kN}$$
$$F_{v,Rk} = 1,885 \text{ kN}$$

The angle bracket is mounted using one specific nail patterns for each of the load directions.

No performance has been determined in relation to ductility of a joint under cyclic testing. The contribution to the performance of structures in seismic zones, therefore, has not been assessed.

No performance has been determined in relation to the joint's stiffness properties - to be used for the analysis of the serviceability limit state.

### 3.11 Aspects related to the performance of the product

3.11.1 Corrosion protection in service class 1 and 2.  
In accordance with ETAG 015 the angle bracket has a zinc coating weight of Z275. The steel employed is S250GD with Z275, S350GD with Z275 or S500GD with Z275, both according to EN 10346.

3.11.2 Corrosion protection in service class 3  
In accordance with Eurocode 5 the angle brackets made from stainless steel 1.4301, 1.4401, 1.4404, 1.4541 and/or 1.4571 according to EN 10088-2 and the nails or bolts shall be produced from stainless steel. Products which are hot dipped galvanized according to EN ISO 1461 with a zinc coating thickness of approximately 55  $\mu\text{m}$  are intended for use in service class 1, 2 and 3 according to EN 1995 (Eurocode 5).

### 3.12 General aspects related to the fitness for use of the product

SIMA Industri connectors are manufactured in accordance with the provisions of this European Technical Assessment using the manufacturing processes as identified in the inspection of the plant by the notified inspection body and laid down in the technical documentation.

The nailing pattern used shall be either the maximum or the minimum pattern as defined in Annex B.

Wane under the flaps of the angle bracket is allowed provided it does not occur under the nails. Wane can reduce the load-bearing capacity of the connection.

A gap between the connector and the timber member is not allowed. However, where the angle bracket is used for a connection between a beam and a column a gap of 5 mm is allowed.

## **4 Attestation and verification of constancy of performance (AVCP)**


### **4.1 AVCP system**

According to the decision 97/638/EC of the European Commission<sup>1</sup>, as amended, the system(s) of assessment and verification of constancy of performance (see Annex V to Regulation (EU) No 305/2011) is 2+.

## **5 Technical details necessary for the implementation of the AVCP system, as foreseen in the applicable EAD**

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at ETA-Danmark

Issued in Copenhagen on 2015-08-30 by



Thomas Bruun  
Managing Director, ETA-Danmark

**Annex A**  
**Changes from last ETA**

<b>Additions and modifications for this ETA</b>	
<b>Pages</b>	<b>Update</b>
	ETA extended
3	Note about stainless steel and hot dipped galvanized added
6	New nail values
12	V1-1 removed
18	Renamed V10 to V10 2,5
17-43	V8 added
18-44	V10 added
21-47	V20 added
22-49	V26 and V27 added
23-53	V170 added
30-56	Characteristic values added to all load carrying value tables

<b>Additions and modifications for the ETA valid from 2013-06-26 to 2015-09-07</b>	
<b>Pages</b>	<b>Update</b>
10	Annex A added
30-56	Formula for F4/F5 directions optimised through the ETA
12,14 and 33,36	V1Ø7 and V2Ø7 added
17,18 and 42,44	V7PL and V10 2,5 added
12	Angle V1 added with smaller height
12-27	Colored hole patterns

<b>Additions and modifications for the ETA valid from 2012-09-07 to 2015-09-07</b>	
<b>Pages</b>	<b>Update</b>
33-35 and 39-41	V2PL and V4PL edited
27 and 51-52	1-150 and K4 added
21,24 and 48-51	V21 and P4 added

<b>Additions and modifications for the ETA valid from 2010-04-09 to 2015-04-09</b>	
<b>Pages</b>	<b>Update</b>
33-3513 and 3139-41	V2PL and V4PL added



**Annex B**  
**Product details and definitions**

Table A1 Fastener specification

Nail, screw and bolt type	Nail and screw size (mm)		Finish	ETA
	Diameter	Length		
Paslode Connector nail	4,0	40	Electroplated zinc	09/0273
Paslode Connector nail	4,0	60	Electroplated zinc	09/0273
Bolt M8	8		For relevant angle brackets see the assumed characteristic capacities of the bolt connection and compare with the specification of the manufacturer	
Bolt M10	10			
Bolt M12	12			
Hexagon head wood screw	6	40		

**Connector specification:**

Holes marked blue and green are used in case of optimal nailing

Holes marked yellow are used in case of bolting

Angle bracket V1, V2, V2PL, V3, V4 and V4PL are marked with numbers referenced from Annex C



V2

Technical drawing of the V2 angle bracket. The drawing includes three views: a front view with dimensions (65 mm width, 90 mm height, 2.5 mm thickness), a side view showing the profile, and a perspective view. The front view shows a central slot with a diameter of 11 mm and a depth of 20 mm. The side view shows a 90-degree angle with a 65 mm horizontal leg and a 90 mm vertical leg. The perspective view shows the bracket's L-shaped profile with a central slot and a series of holes along the edges.

Rev. No.	Date	Correction	Sign.
Date:	29-09-2005	<b>sima</b>	Customer:
Scale:	1:2		T.No:
Sign.:	MG	<small>SIMA Industri ApS                      Industrivej 40                      DK-7490 Aulum                      Tel. +45 97 47 26 11 Fax +45 97 47 37 11  <a href="mailto:Info@sima-industri.dk">Info@sima-industri.dk</a> <a href="http://www.sima-industri.dk">www.sima-industri.dk</a> </small>	Material:
Format:	A4		<small>Copyright                      THIS DRAWING IS THE PROPERTY OF SIMA INDUSTRI A/S AND MUST NOT BE ACCESSIBLE FOR REPRESENTATIVES FROM OTHER COMPANIES</small>
Type:		V2	Art No.:
		90 x 90 x 2,5 x 65 mm m/rib	210780


Additionally, the angle brackets type V2 can be made from 1,5 mm pre-galvanized steel in grades from Grade S350GD to Grade S500GD + min. Z275 according to EN 10346 named V2PL

V2 Stainless


Technical drawing of the V2 Stainless angle bracket. The drawing includes three views: a front view with dimensions (65 mm width, 90 mm height, 2 mm thickness), a side view showing the profile, and a perspective view. The front view shows a central slot with a diameter of 11 mm and a depth of 20 mm. The side view shows a 90-degree angle with a 65 mm horizontal leg and a 90 mm vertical leg. The perspective view shows the bracket's L-shaped profile with a central slot and a series of holes along the edges.

Rev. No.	Date	Correction	Sign.
Date:	06-02-2006	<b>sima</b>	Customer:
Scale:	1:2		T.No:
Sign.:	MG	<small>SIMA Industri ApS                      Industrivej 40                      DK-7490 Aulum                      Tel. +45 97 47 26 11 Fax +45 97 47 37 11  <a href="mailto:Info@sima-industri.dk">Info@sima-industri.dk</a> <a href="http://www.sima-industri.dk">www.sima-industri.dk</a> </small>	Material:
Format:	A4		<small>Copyright                      THIS DRAWING IS THE PROPERTY OF SIMA INDUSTRI A/S AND MUST NOT BE ACCESSIBLE FOR REPRESENTATIVES FROM OTHER COMPANIES</small>
Type:		V2 Stainless	Art No.:
		90 x 90 x 2 x 65 mm m/rib	210809


**V2Ø7**



**V3**




V4




Additionally, the bracket type V4 can be made from 2,0 mm pre-galvanized steel grades from Grade S350GD to Grade S500GD + min. Z275 according to EN 10346 named V4PL


V4 Stainless




V6




V7




V7PL




V8



**V10 2,5**




**V10**







V12




V13




V14




V15



**V20**



**V21**



V26


Date:	27-01-2015	<b>sima</b>	Customer:
Scale:	1:2		T.No:
Sign.:	KHD	SIMA Industri ApS Industrivej Nord 40 DK-7490 Aulum Tel. +45 97 47 26 11 Fax +45 97 47 37 11 Mail:sima@simaindustrial.dk www:simaindustri.dk	Material:
Format:	A4		S250 GD Z275 MA
Copyright THIS DRAWING IS THE PROPERTY OF SIMA INDUSTRI A/S AND MUST NOT BE ACCESSIBLE FOR REPRESENTATIVES FROM OTHER COMPANIES		Type:	Art Nr.:
		V26 190 x 50 x 2 x 40 mm	212779

V27


Date:	27-01-2015	<b>sima</b>	Customer:
Scale:	1:2		T.No:
Sign.:	KHD	SIMA Industri ApS Industrivej Nord 40 DK-7490 Aulum Tel. +45 97 47 26 11 Fax +45 97 47 37 11 Mail:sima@simaindustrial.dk www:simaindustri.dk	Material:
Format:	A4		S250 GD Z275 MA EN 10326 : 2004
Copyright THIS DRAWING IS THE PROPERTY OF SIMA INDUSTRI A/S AND MUST NOT BE ACCESSIBLE FOR REPRESENTATIVES FROM OTHER COMPANIES		Type:	Art Nr.:
		V27 290 x 50 x 2 x 40 mm	212780




**P4**




**P1-8**




**P1-10**




**P1-12**



**P2-10**



**P2-12**





1-150

Rev. No.	Date	Correction	Sign.
	07-10-2005		
Scale:	1:2		Customer:
Sign.:			T.No.:
Format:			Material:
Copyright © 2005 SIMA s.p.a. - Tutti i diritti sono riservati.		Type:	Art. Nr.:
		1-150 150 x 75 x 5 x 40 mm	S 235 JRG2 - EN 10025 DIN 1017 Hot dip galv. 211092

K4

Rev. No.	Date	Correction	Sign.
	04-10-2005		
Scale:	1:2		Customer:
Sign.:			T.No.:
Format:			Material:
Copyright © 2005 SIMA s.p.a. - Tutti i diritti sono riservati.		Type:	Art. Nr.:
		K4 145 x 83 x 3 x 80 mm	S 250GD 2275 MA EN 10326 : 2004 211561

## Annex C

### Characteristic load-carrying capacity

#### Design Basis - general

##### Combined forces

For practical purposes the strength verification is always carried out for design forces and design capacities. If the forces are combined the following inequalities shall be fulfilled:

$$\left(\frac{F_{1,d}}{R_{1,d}}\right)^2 + \left(\frac{F_{2,d}}{R_{2,d}}\right)^2 + \left(\frac{F_{3,d}}{R_{3,d}}\right)^2 \leq 1$$

The forces  $F_{2,d}$  and  $F_{3,d}$  are forces with opposite direction. Only the one with a value shall be inserted while the other shall be set to zero.

$$\frac{F_{1,d}}{R_{1,d}} + \frac{F_{4,d}}{R_{4,d}} + \frac{F_{5,d}}{R_{5,d}} \leq 1$$

The forces  $F_{4,d}$  and  $F_{5,d}$  are forces with opposite direction. Only the one with a value shall be inserted while the other shall be set to zero.

In case of a combination where forces work in 3 directions the following formula are to be used:

$$\sqrt{\left[\frac{F_{1,d}}{R_{1,d}} + \frac{F_{4,d/5,d}}{R_{4,d/5,d}}\right]^2 + \left[\frac{F_{2,d/3,d}}{R_{2,d/3,d}}\right]^2} \leq 1$$

##### Timber splitting

For the lifting force  $F_1$  it must be checked that splitting will not occur in accordance with Eurocode 5 or a similar national Timber Code.

##### Density

The load-carrying capacities of the angle bracket connections are stated for a characteristic density of 350 kg/m<sup>3</sup>.

For timber or wood based material with a lower characteristic density than 350 kg/m<sup>3</sup> the load-carrying capacities shall be reduced by the  $k_{\text{dens}}$  factor:

$$k_{\text{dens}} = \left(\frac{\rho_k}{350}\right)^2$$

Where  $\rho_k$  is the characteristic density of the timber in kg/m<sup>3</sup>.

**Angle Bracket V1, V1Ø7, V2, V2PL, V2 stainless, V2Ø7, V3, V4, V4PL, V4 stainless, V6, V7, V7PL, V8, V10 2,5, V10, V12, V13, V14, V15, V20, V21, V170, P4, K4, LV1, 1-150**

**Design Basis**




Figure 1. Forces, 1 bracket: wood to concrete




Figure 2. Forces, 2 brackets: wood to concrete




Figure 3. Forces, 2 brackets: beam to beam

**Two angle brackets per connection**

The angle brackets must be placed on each side of the beam opposite of each other

**Acting forces**

- F<sub>1</sub>            Lifting force acting along the central axis of the joint.
- F<sub>2</sub> and F<sub>3</sub>    Lateral force acting in the joint between the purlin and beam in the purlin direction.
- F<sub>4</sub> and F<sub>5</sub>    Lateral force acting in the beam direction along the central axis of the joint but elevated e above the beam.

**One angle bracket per connection**

**Acting forces**

- F<sub>4</sub>            Lateral force acting in the beam direction perpendicular to the vertical flap elevated e above the beam directed towards the angle brackets vertical flap
- F<sub>5</sub>            Lateral force acting in the beam direction perpendicular to the vertical flap elevated e above the beam directed away from the angle brackets vertical flap

**Wane**

For F<sub>1</sub>, F<sub>2</sub> and F<sub>3</sub> wane is allowed on the side towards the angle bracket with an extent from the bottom to the lower row of nails. For all other forces wane is not allowed under the angle bracket.

**Note:**

The characteristic values stated below for connections with 2,5 mm thick brackets type V2 made from pre-galvanized steel Grade S250GD + min. Z275 according to EN 10346 can be applied to connections made with 1,5 mm thick brackets type V2 made from pre-galvanized steel in grades from Grade S350GD to Grade S500GD + min. Z275 according to EN 10346 named V2PL.

Similarly, the characteristic values stated below for connections with 3,0 mm thick brackets type V4 made from pre-galvanized steel Grade S250GD + min. Z275 according to EN 10346 can be applied to connections made with 2,0 mm thick brackets type V4 made from pre-galvanized steel in grades from Grade S350GD to Grade S500GD + min. Z275 according to EN 10346 named V4PL.

The values have been assessed in accordance with EC 5 Table 3.1- "Values of  $K_{mod}$ " where needed.

**1 angle bracket V1, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F4, [kN]	F5, [kN]
12,13,14,15,16	5 nails	P	25,4/e, max ↓ 20,63	1,85*(2,5+b)/e, max ↓ 1,07
		L	25,4/e, max ↓ 20,63	2,16*(2,5+b)/e, max ↓ 1,25
		M	25,4/e, max ↓ 20,63	2,47*(2,5+b)/e, max ↓ 1,42
Holes marked yellow	3 bolts	S	25,4/e, max ↓ 20,63	2,78*(2,5+b)/e, max ↓ 1,60
		I	25,4/e, max ↓ 20,63	3,40*(2,5+b)/e, max ↓ 1,96
Characteristic values, b and e in mm			25,4/e, max ↓ 20,63	3,09*(2,5+b)/e, max ↓ 1,78

**2 angle brackets V1, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]
12,13,14,15,16	10 nails	P	2,45	19,24
		L	2,86	22,44
		M	3,26	25,65
Holes marked yellow	6 bolts	S	3,67	28,85
		I	4,49	35,27
Characteristic values			4,08	32,06

**2 angle brackets V1, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4	16	P	2,03	4,40	$0,47 \cdot (29,6+b)/e$ , max ↓ 5,36
		L	2,37	5,13	$0,55 \cdot (29,6+b)/e$ , max ↓ 6,25
		M	2,71	5,86	$0,62 \cdot (29,6+b)/e$ , max ↓ 7,14
		S	3,05	6,60	$0,70 \cdot (29,6+b)/e$ , max ↓ 8,04
		I	3,73	8,06	$0,86 \cdot (29,6+b)/e$ , max ↓ 9,82
8,11,15,16					
Characteristic values, b and e in mm			3,38	7,33	$0,78 \cdot (29,6+b)/e$ , max ↓ 8,93

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4	20	P	4,07	4,40	$0,47 \cdot (29,6+b)/e$ , max ↓ 8,04
		L	4,75	5,13	$0,55 \cdot (29,6+b)/e$ , max ↓ 9,38
		M	5,42	5,86	$0,62 \cdot (29,6+b)/e$ , max ↓ 10,72
		S	6,10	6,60	$0,70 \cdot (29,6+b)/e$ , max ↓ 12,06
		I	7,46	8,06	$0,86 \cdot (29,6+b)/e$ , max ↓ 14,74
8,9,10,11,15,16					
Characteristic values, b and e in mm			6,78	7,33	$0,78 \cdot (29,6+b)/e$ , max ↓ 13,40

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4,5,6	30	P	4,07	6,31	$0,47 \cdot (29,6+b)e$ , max ↓ 12,05
		L	4,75	7,36	$0,55 \cdot (29,6+b)/e$ , max ↓ 14,06
		M	5,42	8,41	$0,62 \cdot (29,6+b)/e$ , max ↓ 16,07
		S	6,10	9,46	$0,70 \cdot (29,6+b)/e$ , max ↓ 18,08
		I	7,46	11,56	$0,86 \cdot (29,6+b)/e$ , max ↓ 22,10
8,9,10,11,12,13,14,15,16					
Characteristic values, b and e in mm			6,78	10,52	$0,78 \cdot (29,6+b)/e$ , max ↓ 20,08

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4  8,11,15,16	16	P	3,78	4,40	$0,87 \cdot (15,9+b)/e$ , max ↓ 5,36
		L	4,41	5,13	$1,02 \cdot (15,9+b)/e$ , max ↓ 6,25
		M	5,04	5,86	$1,16 \cdot (15,9+b)/e$ , max ↓ 7,14
		S	5,67	6,60	$1,31 \cdot (15,9+b)/e$ , max ↓ 8,04
		I	6,93	8,06	$1,60 \cdot (15,9+b)/e$ , max ↓ 9,82
Characteristic values, b and e in mm			6,30	7,33	$1,45 \cdot (15,9+b)/e$ , max ↓ 8,93

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4  8,9,10,11,15,16	20	P	5,01	4,40	$0,87 \cdot (15,9+b)/e$ , max ↓ 8,04
		L	5,85	5,13	$1,02 \cdot (15,9+b)/e$ , max ↓ 9,38
		M	6,68	5,86	$1,16 \cdot (15,9+b)/e$ , max ↓ 10,72
		S	7,52	6,60	$1,31 \cdot (15,9+b)/e$ , max ↓ 12,06
		I	9,19	8,06	$1,60 \cdot (15,9+b)/e$ , max ↓ 14,74
Characteristic values, b and e in mm			8,36	7,33	$1,45 \cdot (15,9+b)/e$ , max ↓ 13,40

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4,5,6  8,9,10,11,12,13,14,15,16	30	P	6,78	6,31	$0,87 \cdot (15,9+b)/e$ , max ↓ 12,05
		L	7,91	7,36	$1,02 \cdot (15,9+b)/e$ , max ↓ 14,06
		M	9,04	8,41	$1,16 \cdot (15,9+b)/e$ , max ↓ 16,06
		S	10,17	9,46	$1,31 \cdot (15,9+b)/e$ , max ↓ 18,08
		I	12,43	11,56	$1,60 \cdot (15,9+b)/e$ , max ↓ 22,10
Characteristic values, b and e in mm			11,30	10,51	$1,45 \cdot (15,9+b)/e$ , max ↓ 20,09

**2 angle brackets V1Ø7**

M6 Hexagon wood screw	No. of screws pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked yellow	4 bolts	P	1,87	0,49	$0,93*(2,5+b)/e$ , max ↓ 1,87
		L	2,18	0,57	$1,09*(2,5+b)/e$ , max ↓ 2,18
		M	2,49	0,66	$1,24*(2,5+b)/e$ , max ↓ 2,49
	8 bolts	S	2,80	0,74	$1,40*(2,5+b)/e$ , max ↓ 2,80
		I	3,42	0,90	$1,71*(2,5+b)/e$ , max ↓ 3,42
Characteristic values, b and e in mm			3,11	0,81	$1,55*(2,5+b)/e$ , max ↓ 3,11

**1 angle bracket V2 and V2PL, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F4, [kN]	F5, [kN]
2,3,4,5,6,7,8,9  Hole marked yellow	8 nails	P	$25,4/e$ , max ↓ 20,63	$1,53*(2,5+b)/e$ , max ↓ 1,22
		L	$25,4/e$ , max ↓ 20,63	$1,74*(2,5+b)/e$ , max ↓ 1,42
		M	$25,4/e$ , max ↓ 20,63	$2,04*(2,5+b)/e$ , max ↓ 1,62
	1 bolt	S	$25,4/e$ , max ↓ 20,63	$2,30*(2,5+b)/e$ , max ↓ 1,83
		I	$25,4/e$ , max ↓ 20,63	$2,81*(2,5+b)/e$ , max ↓ 2,23
Characteristic values, b and e in mm			$25,4/e$ , max ↓ 20,63	$2,55*(2,5+b)/e$ , max ↓ 2,03

**1 angle bracket V2 and V2PL, beam to beam connection**

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
2,3,4,5,6,7,8,9  11,12,13,14,15,16, 17,18,19,20	18	P	1,75	2,87	$25,4/e$ , max ↓ 6,41	$6,41*(37,5+b)/e$ , max ↓ 1,75
		L	2,04	3,35	$25,4/e$ , max ↓ 7,48	$7,48*(37,5+b)/e$ , max ↓ 2,04
		M	2,34	3,82	$25,4/e$ , max ↓ 8,55	$8,55*(37,5+b)/e$ , max ↓ 2,34
		S	2,63	4,30	$25,4/e$ , max ↓ 9,62	$9,62*(37,5+b)/e$ , max ↓ 2,63
		I	3,21	5,26	$25,4/e$ , max ↓ 11,76	$11,76*(37,5+b)/e$ , max ↓ 3,21
Characteristic values, b and e in mm			2,91	4,78	$25,4/e$ , max ↓ 10,68	$10,69*(37,5+b)/e$ , max ↓ 2,92

**2 angle brackets V2 and V2PL, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]
2,3,4,5,6,7,8,9	16 nails	P	0,76	5,17
		L	0,89	6,03
		M	1,02	6,90
Holes marked yellow	2 bolts	S	1,14	7,76
		I	1,40	9,48
Characteristic values			1,27	8,62

**2 angle brackets V2 and V2PL, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
2,3,4,5,6,7,8,9	36	P	5,58	8,70	$2,10 \cdot (41,1+b)/e$ , max ↓ 9,42
		L	6,51	10,15	$2,45 \cdot (41,1+b)/e$ , max ↓ 10,99
		M	7,44	11,60	$2,80 \cdot (41,1+b)/e$ , max ↓ 12,56
S		8,37	13,05	$3,15 \cdot (41,1+b)/e$ , max ↓ 14,13	
I		10,23	15,95	$3,85 \cdot (41,1+b)/e$ , max ↓ 17,27	
11,12,13,14,15,16, 17,18,19,20					
Characteristic values, b and e in mm			9,30	14,50	$3,50 \cdot (41,1+b)/e$ , max ↓ 15,70

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
2,5,6,9	16	P	4,07	4,33	$0,94 \cdot (65+b)/e$ , max ↓ 5,36
		L	4,75	5,05	$1,09 \cdot (65+b)/e$ , max ↓ 6,25
		M	5,42	5,78	$1,25 \cdot (65+b)/e$ , max ↓ 7,14
S		6,10	6,50	$1,40 \cdot (65+b)/e$ , max ↓ 8,04	
I		7,46	7,94	$1,72 \cdot (65+b)/e$ , max ↓ 9,82	
11,15,16,20					
Characteristic values, b and e in mm			6,78	7,22	$1,56 \cdot (65+b)/e$ , max ↓ 8,93



Paslode Connector nails 4,0 x 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
2,3,4,5,6,7,8,9  11,12,13,15,16, 17,18,20	32	P	7,33	7,98	$1,69 \cdot (47,5+b)/e$ , max ↓ 10,72
		L	8,55	9,31	$1,97 \cdot (47,5+b)/e$ , max ↓ 12,50
		M	9,78	10,64	$2,25 \cdot (47,5+b)/e$ , max ↓ 14,29
		S	11,00	11,97	$2,53 \cdot (47,5+b)/e$ , max ↓ 16,07
		I	13,44	14,63	$3,09 \cdot (47,5+b)/e$ , max ↓ 19,65
Characteristic values, b and e in mm			12,22	13,30	$2,81 \cdot (47,5+b)/e$ , max ↓ 17,86

Paslode Connector nails 4,0 x 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
2,3,4,5,6,7,8,9  11,12,13,14,15,16, 17,18,19,20	36	P	9,66	8,52	$2,1 \cdot (41,1+b)/e$ , max ↓ 9,06
		L	11,27	9,94	$2,45 \cdot (41,1+b)/e$ , max ↓ 10,5
		M	12,88	11,36	$2,8 \cdot (41,1+b)/e$ , max ↓ 12,08
		S	14,49	12,78	$3,15 \cdot (41,1+b)/e$ , max ↓ 13,59
		I	17,71	15,62	$3,85 \cdot (41,1+b)/e$ , max ↓ 16,61
Characteristic values, b and e in mm			16,10	14,20	$3,50 \cdot (41,1+b)/e$ , max ↓ 15,10

## 2 angle brackets V2 Stainless, beam to beam connection

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	36	P	4,79	6,91	$2,4 \cdot (22+b)/e$ , max ↓ 7,73
		L	5,59	8,06	$2,8 \cdot (22+b)/e$ , max ↓ 9,02
		M	6,38	9,22	$3,2 \cdot (22+b)/e$ , max ↓ 10,31
		S	7,18	10,37	$3,6 \cdot (22+b)/e$ , max ↓ 11,60
		I	8,78	12,67	$4,4 \cdot (22+b)/e$ , max ↓ 14,18
Characteristic values, b and e in mm			7,98	11,52	$4,0 \cdot (22+b)/e$ , max ↓ 12,89

**2 angle brackets V2Ø7**

M6 Hexagon wood screw	No. of screws pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked yellow	8 bolts	P	1,87	1,51	$0,93 \cdot (15,9+b)/e$ , max ↓ 1,87
		L	2,18	1,76	$1,09 \cdot (15,9+b)/e$ , max ↓ 2,18
		M	2,49	2,02	$1,24 \cdot (15,9+b)/e$ , max ↓ 2,49
	8 bolts	S	2,80	2,27	$1,40 \cdot (15,9+b)/e$ , max ↓ 2,80
		I	3,42	2,77	$1,71 \cdot (15,9+b)/e$ , max ↓ 3,42
Characteristic values, b and e in mm			3,11	2,52	$1,55 \cdot (15,9+b)/e$ , max ↓ 3,11

**1 angle bracket V3, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F4, [kN]	F5, [kN]
Holes marked yellow	8 nails	P	$50,6/e$ , max ↓ 54,75	$3,63 \cdot (3+b)/e$ , max ↓ 1,04
		L	$50,6/e$ , max ↓ 54,75	$4,24 \cdot (3+b)/e$ , max ↓ 1,22
		M	$50,6/e$ , max ↓ 54,75	$4,84 \cdot (3+b)/e$ , max ↓ 1,39
	3 bolts	S	$50,6/e$ , max ↓ 54,75	$5,45 \cdot (3+b)/e$ , max ↓ 1,57
		I	$50,6/e$ , max ↓ 54,75	$6,65 \cdot (3+b)/e$ , max ↓ 1,91
Characteristic values, b and e in mm			$50,6/e$ , max ↓ 54,75	$6,05 \cdot (3+b)/e$ , max ↓ 1,74

**2 angle brackets V3, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked yellow	16 nails	P	9,61	5,49	$30,36/e$ , max ↓ 54,75
		L	9,61	6,41	$35,42/e$ , max ↓ 54,75
		M	9,61	7,32	$40,48/e$ , max ↓ 54,75
	6 bolts	S	9,61	8,24	$45,54/e$ , max ↓ 54,75
		I	9,61	10,07	$55,66/e$ , max ↓ 54,75
Characteristic values, b and e in mm			9,61	9,15	$50,60/e$ , max ↓ 54,75

**2 angle brackets V3, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,8,9  11,16,23,24	16	P	2,08	4,97	$0,48 \cdot (57,8+b)/e$ , max ↓ 5,36
		L	2,42	5,80	$0,56 \cdot (57,8+b)/e$ , max ↓ 6,25
		M	2,77	6,62	$0,64 \cdot (57,8+b)/e$ , max ↓ 7,14
		S	3,11	7,45	$0,72 \cdot (57,8+b)/e$ , max ↓ 8,04
		I	3,81	9,11	$0,88 \cdot (57,8+b)/e$ , max ↓ 9,82
Characteristic values, b and e in mm			3,46	8,28	$0,80 \cdot (57,8+b)/e$ , max ↓ 8,93

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,5,6,8,9  11,12,15,16,23,24	24	P	4,15	7,03	$0,95 \cdot (28,9+b)/e$ , max ↓ 8,04
		L	4,84	8,20	$1,11 \cdot (28,9+b)/e$ , max ↓ 9,38
		M	5,53	9,38	$1,27 \cdot (28,9+b)/e$ , max ↓ 10,72
		S	6,22	10,55	$1,43 \cdot (28,9+b)/e$ , max ↓ 12,06
		I	7,60	12,89	$1,75 \cdot (28,9+b)/e$ , max ↓ 14,74
Characteristic values, b and e in mm			6,91	11,72	$1,59 \cdot (28,9+b)/e$ , max ↓ 13,40

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4,5,6  11,12,13,14,15,16,23,24	28	P	6,22	5,53	$1,43 \cdot (19,3+b)/e$ , max ↓ 10,72
		L	7,25	6,45	$1,67 \cdot (19,3+b)/e$ , max ↓ 12,50
		M	8,29	7,37	$1,91 \cdot (19,3+b)/e$ , max ↓ 14,29
		S	9,32	8,29	$2,15 \cdot (19,3+b)/e$ , max ↓ 16,07
		I	11,40	10,13	$2,63 \cdot (19,3+b)/e$ , max ↓ 19,65
Characteristic values, b and e in mm			10,36	9,21	$2,39 \cdot (19,3+b)/e$ , max ↓ 17,86

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4,5,6  11,12,13,14,15, 16,21,22,23,24	38	P	6,22	10,38	$1,43 \cdot (19,3+b)/e$ , max ↓ 13,40
		L	7,25	12,11	$1,67 \cdot (19,3+b)/e$ , max ↓ 15,63
		M	8,29	13,84	$1,91 \cdot (19,3+b)/e$ , max ↓ 17,86
		S	9,32	15,57	$2,15 \cdot (19,3+b)/e$ , max ↓ 20,10
		I	11,40	19,03	$2,63 \cdot (19,3+b)/e$ , max ↓ 24,56
Characteristic values, b and e in mm			10,36	17,30	$2,39 \cdot (19,3+b)/e$ , max ↓ 22,33

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,8,9  11,16,23,24	16	P	3,85	4,97	$0,89 \cdot (31,2+b)/e$ , max ↓ 5,36
		L	4,49	5,80	$1,03 \cdot (31,2+b)/e$ , max ↓ 6,25
		M	5,13	6,62	$1,18 \cdot (31,2+b)/e$ , max ↓ 7,14
		S	5,77	7,45	$1,33 \cdot (31,2+b)/e$ , max ↓ 8,04
		I	7,05	9,11	$1,63 \cdot (31,2+b)/e$ , max ↓ 9,82
Characteristic values, b and e in mm			6,41	8,28	$1,48 \cdot (31,2+b)/e$ , max ↓ 8,93

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,5,6,8,9  11,12,15,16,23,24	24	P	7,70	7,03	$1,77 \cdot (15,6+b)/e$ , max ↓ 8,04
		L	8,98	8,20	$2,06 \cdot (15,6+b)/e$ , max ↓ 9,38
		M	10,26	9,38	$2,36 \cdot (15,6+b)/e$ , max ↓ 10,72
		S	11,55	10,55	$2,65 \cdot (15,6+b)/e$ , max ↓ 12,06
		I	14,11	12,89	$3,42 \cdot (15,6+b)/e$ , max ↓ 14,74
Characteristic values, b and e in mm			12,83	11,72	$2,95 \cdot (15,6+b)/e$ , max ↓ 13,40

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4,5,6  11,12,13,14,15,16,23,24	28	P	10,02	5,53	2,30*(12+b)/e, max ↓ 10,72
		L	11,69	6,45	2,70*(12+b)/e, max ↓ 12,50
		M	13,36	7,37	3,07*(12+b)/e, max ↓ 14,29
		S	15,03	8,29	3,45*(12+b)/e, max ↓ 16,07
		I	18,37	10,13	4,22*(12+b)/e, max ↓ 19,65
Characteristic values, b and e in mm			16,70	9,22	3,84*(12+b)/e, max ↓ 17,87

**1 angle bracket V4 and V4PL, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F4, [kN]	F5, [kN]
Vertical flap fully nailed	14 nails	P	50,6/e, max ↓ 54,75	3,89*(3+b)/e, max ↓ 1,52
		L	50,6/e, max ↓ 54,75	4,54*(3+b)/e, max ↓ 1,77
		M	50,6/e, max ↓ 54,75	5,19*(3+b)/e, max ↓ 2,02
Holes marked yellow	3 bolts	S	50,6/e, max ↓ 54,75	5,84*(3+b)/e, max ↓ 2,28
		I	50,6/e, max ↓ 54,75	7,14*(3+b)/e, max ↓ 2,78
Characteristic values, b and e in mm			50,6/e, max ↓ 54,75	6,49*(3+b)/e, max ↓ 2,53

**1 angle bracket V4 and V4PL, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Fully nailed	22	P	1,75	2,83	47,8/e, max ↓ 8,55	8,55*(33+b)/e, max ↓ 0,88
		L	2,04	3,30	47,8/e, max ↓ 8,55	9,98*(33+b)/e, max ↓ 1,02
		M	2,34	3,77	47,8/e, max ↓ 8,55	11,40*(33+b)/e, max ↓ 1,17
		S	2,63	4,24	47,8/e, max ↓ 8,55	12,83*(33+b)/e, max ↓ 1,31
		I	3,21	5,18	47,8/e, max ↓ 8,55	15,68*(33+b)/e, max ↓ 1,61
Characteristic values, b and e in mm			2,92	4,72	47,8/e, max ↓ 8,55	14,25*(33+b)/e, max ↓ 1,46

**2 angle brackets V4 and V4PL, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]
Vertical flap fully nailed	28 nails	P	5,29	29,93
		L	6,17	34,92
		M	7,06	39,90
Holes marked yellow	6 bolts	S	7,94	44,89
		I	9,70	54,87
Characteristic values			8,82	49,88

**2 angle brackets V4 and V4PL, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F2 /F3, [kN]
1,3,4,5,6,8	24	P	7,48
		L	8,73
		M	9,98
S		11,22	
9,10,15,16,17,22		I	13,72
Characteristic values			12,47

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4,5,6,7,8	32	P	9,9	9,68	$2,62 \cdot (56,3+b)/e$ , max ↓ 9,06
		L	11,55	11,30	$3,09 \cdot (56,3+b)/e$ , max ↓ 10,57
		M	13,20	12,91	$3,54 \cdot (56,3+b)/e$ , max ↓ 12,08
		S	14,85	14,53	$3,98 \cdot (56,3+b)/e$ , max ↓ 13,59
		9,10,11,15,16,17,18,22	I	18,15	17,75
Characteristic values, b and e in mm			16,50	16,14	$4,42 \cdot (56,3+b)/e$ , max ↓ 15,10

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4,5,6,7,8  9,10,15,16,17,22	24	P	8,14	7,48	$1,87 \cdot (73,5+b)/e$ , max ↓ 8,04
		L	9,50	8,73	$2,18 \cdot (73,5+b)/e$ , max ↓ 9,38
		M	10,86	9,98	$2,50 \cdot (73,5+b)/e$ , max ↓ 10,72
		S	12,21	11,22	$2,81 \cdot (73,5+b)/e$ , max ↓ 12,06
		I	14,93	13,72	$3,43 \cdot (73,5+b)/e$ , max ↓ 14,74
Characteristic values, b and e in mm			13,57	12,47	$3,12 \cdot (73,5+b)/e$ , max ↓ 13,40

Paslode Connector nails 4,0 × 60 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
1,2,3,4,5,6,7,8  9,10,11,15,16,17,18,22	32	P	13,32	9,84	$2,62 \cdot (56,3+b)/e$ , max ↓ 10,26
		L	15,54	11,48	$3,09 \cdot (56,3+b)/e$ , max ↓ 11,97
		M	17,76	13,12	$3,54 \cdot (56,3+b)/e$ , max ↓ 13,68
		S	19,98	14,76	$3,98 \cdot (56,3+b)/e$ , max ↓ 15,39
		I	24,42	18,04	$4,86 \cdot (56,3+b)/e$ , max ↓ 18,81
Characteristic values, b and e in mm			22,20	16,40	$4,42 \cdot (56,3+b)/e$ , max ↓ 17,10

## 2 angle brackets V4 Stainless, beam to beam connection

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	44	P	4,79	6,80	$2,4 \cdot (17,5+b)/e$ , max ↓ 10,31
		L	5,59	7,94	$2,8 \cdot (17,5+b)/e$ , max ↓ 12,03
		M	6,38	9,07	$3,2 \cdot (17,5+b)/e$ , max ↓ 13,75
		S	7,18	10,21	$3,6 \cdot (17,5+b)/e$ , max ↓ 15,47
		I	8,78	12,47	$4,4 \cdot (17,5+b)/e$ , max ↓ 18,91
Characteristic values, b and e in mm			7,98	11,34	$4,0 \cdot (17,5+b)/e$ , max ↓ 17,19

**2 angle brackets V6, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	18	P	3,42	3,07	$1,96*(20,5+b)/e$ or $2,26*(2+b)/e$ , max ↓ 5,66
		L	3,42	3,58	$2,29*(20,5+b)/e$ or $2,64*(2+b)/e$ , max ↓ 6,60
		M	3,42	4,09	$2,61*(20,5+b)/e$ or $3,02*(2+b)/e$ , max ↓ 7,54
		S	3,42	4,60	$2,94*(20,5+b)/e$ or $3,39*(2+b)/e$ , max ↓ 8,49
		I	3,42	5,62	$3,60*(20,5+b)/e$ or $4,15*(2+b)/e$ , max ↓ 10,37
Characteristic values, b and e in mm			3,42	5,11	$3,27*(20,5+b)/e$ or $3,77*(2+b)/e$ , max ↓ 9,43

**2 angle brackets V7, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	16	P	2,39	3,07	$1,2*(17+b)/e$ , max ↓ 4,52
		L	2,79	3,58	$1,4*(17+b)/e$ , max ↓ 5,28
		M	3,19	4,09	$1,6*(17+b)/e$ , max ↓ 6,03
		S	3,59	4,60	$1,8*(17+b)/e$ , max ↓ 6,79
		I	4,39	5,62	$2,2*(17+b)/e$ , max ↓ 8,29
Characteristic values, b and e in mm			3,99	5,11	$2,0*(17+b)/e$ , max ↓ 7,53

**2 angle brackets V7PL, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	16	P	2,39	3,07	$1,2*(16,5+b)/e$ , max ↓ 4,52
		L	2,79	3,58	$1,4*(16,5+b)/e$ , max ↓ 5,28
		M	3,19	4,09	$1,6*(16,5+b)/e$ , max ↓ 6,03
		S	3,59	4,60	$1,8*(16,5+b)/e$ , max ↓ 6,79
		I	4,39	5,62	$2,2*(16,5+b)/e$ , max ↓ 8,29
Characteristic values, b and e in mm			3,99	5,11	$2,0*(16,5+b)/e$ , max ↓ 7,53



**1 angle bracket V8, wood to concrete connection**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked green	4 nails	P	1,98	1,90	21,5/e max ↓ 5,35	1,33
		L	1,98	1,90	21,5/e max ↓ 6,24	1,33
		M	1,98	1,90	21,5/e max ↓ 7,13	1,33
Hole marked yellow	1 bolt	S	1,98	1,90	21,5/e max ↓ 8,02	1,33
		I	1,98	1,90	21,5/e max ↓ 9,80	1,33
Characteristic values, b and e in mm			1,98	1,90	21,5/e max ↓ 8,91	1,33

**1 angle bracket V8, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	10 nails	P	1,75	1,98	21,5/e max ↓ 5,35	1,33
		L	2,04	2,31	21,5/e max ↓ 6,24	1,33
		M	2,32	2,64	21,5/e max ↓ 7,13	1,33
		S	2,61	2,97	21,5/e max ↓ 8,02	1,33
		I	3,19	3,63	21,5/e max ↓ 9,80	1,33
Characteristic values, b and e in mm			2,90	3,30	21,5/e max ↓ 8,91	1,33

**2 angle brackets V8, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	20 nails	P	3,48	3,96	1,85*(15+b)/e, max ↓ 5,63
		L	4,06	4,62	2,16*(15+b)/e, max ↓ 6,57
		M	4,64	5,28	2,46*(15+b)/e, max ↓ 7,50
		S	5,22	5,94	2,77*(15+b)/e, max ↓ 8,44
		I	6,38	7,26	3,39*(15+b)/e, max ↓ 10,32
Characteristic values, b and e in mm			5,80	6,60	3,08*(15+b)/e, max ↓ 9,38

**1 angle bracket V10 2,5, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	8	P	1,2	1,03	15,6/e, max ↓ 2,63	4,52*(2,5+b)/e, max ↓ 1,2
		L	1,4	1,20	15,6/e, max ↓ 3,07	5,28*(2,5+b)/e, max ↓ 1,4
		M	1,6	1,37	15,6/e, max ↓ 3,50	6,03*(2,5+b)/e, max ↓ 1,6
		S	1,6	1,55	15,6/e, max ↓ 3,94	6,79*(2,5+b)/e, max ↓ 1,6
		I	1,6	1,89	15,6/e, max ↓ 4,82	8,29*(2,5+b)/e, max ↓ 1,6
Characteristic values, b and e in mm			1,6	1,72	15,6/e, max ↓ 4,38	7,54*(2,5+b)/e, max ↓ 1,6

**2 angle brackets V10 2,5, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	16	P	2,39	2,07	1,2*(21+b)/e, max ↓ 4,52
		L	2,79	2,42	1,4*(21+b)/e, max ↓ 5,28
		M	3,19	2,76	1,6*(21+b)/e, max ↓ 6,03
		S	3,19	3,11	1,8*(21+b)/e, max ↓ 6,79
		I	3,19	3,80	2,2*(21+b)/e, max ↓ 8,29
Characteristic values, b and e in mm			3,19	3,45	2,0*(21+b)/e, max ↓ 7,54

**1 angle bracket V10, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	8	P	1,23	0,49	22,5/e, max ↓ 2,61	1,23
		L	1,44	0,57	22,5/e, max ↓ 3,05	1,44
		M	1,64	0,66	22,5/e, max ↓ 3,48	1,64
		S	1,85	0,75	22,5/e, max ↓ 3,92	1,85
		I	2,26	0,90	22,5/e, max ↓ 4,79	2,26
Characteristic values, b and e in mm			2,05	0,82	22,5/e, max ↓ 4,35	2,05

**2 angle brackets V10, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	16	P	2,47	0,98	1,23*(19,5+b)/e max ↓ 4,51
		L	2,88	1,15	1,44*(19,5+b)/e max ↓ 5,26
		M	3,29	1,31	1,64*(19,5+b)/e max ↓ 6,01
		S	3,70	1,48	1,85*(19,5+b)/e max ↓ 6,76
		I	4,52	1,80	2,26*(19,5+b)/e max ↓ 8,26
Characteristic values, b and e in mm			4,11	1,64	2,05*(19,5+b)/e max ↓ 7,51

**1 angle bracket V12, beam to concrete connection**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	6 nails	P	1,86	1,96	28,10/e, max ↓ 16,26	6,41*b/e, max ↓ 1,58
		L	1,86	2,29	28,10/e, max ↓ 16,26	7,48*b/e, max ↓ 1,58
		M	1,86	2,62	28,10/e, max ↓ 16,26	8,55*b/e, max ↓ 1,58
Hole marked yellow	1 bolt	S	1,86	2,94	28,10/e, max ↓ 16,26	9,62*b/e, max ↓ 1,58
		I	1,86	3,60	28,10/e, max ↓ 16,26	11,76*b/e, max ↓ 1,58
Characteristic values, b and e in mm			1,86	3,27	28,10/e, max ↓ 16,26	10,69*b/e, max ↓ 1,58

**2 angle brackets V12, beam to concrete connection**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	12 nails	P	3,72	3,92	10,42
		L	3,72	4,58	12,15
		M	3,72	5,23	13,89
Holes marked yellow	2 bolts	S	3,72	5,89	15,62
		I	3,72	7,19	19,09
Characteristic values			3,72	6,54	17,35

**1 angle bracket V12, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	10	P	0,88	1,68	16,86/e, max ↓ 2,14	6,41*b/e, max ↓ 1,58
		L	1,02	1,96	19,67/e, max ↓ 2,14	7,48*b/e, max ↓ 1,58
		M	1,17	2,24	22,48/e, max ↓ 2,14	8,55*b/e, max ↓ 1,58
		S	1,31	2,52	25,49/e, max ↓ 2,14	9,62*b/e, max ↓ 1,58
		I	1,61	3,08	30,91/e, max ↓ 2,14	11,76*b/e, max ↓ 1,58
Characteristic values, b and e in mm			1,46	2,80	28,10/e, max ↓ 2,14	10,69*b/e, max ↓ 1,58

**2 angle brackets V12, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	20	P	2,39	3,55	1,2*(21+b)/e, max ↓ 2,26
		L	2,79	4,14	1,4*(21+b)/e, max ↓ 2,64
		M	3,19	4,74	1,6*(21+b)/e, max ↓ 3,02
		S	3,59	5,33	1,8*(21+b)/e, max ↓ 3,39
		I	4,39	6,51	2,2*(21+b)/e, max ↓ 4,15
Characteristic values, b and e in mm			3,99	5,92	2,0*(21+b)/e, max ↓ 3,76

**2 angle brackets V13, beam to beam connection**

Paslode Connector nails 4,0 x 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	24	P	2,39	4,95	1,2*(22+b)/e, max ↓ 2,26
		L	2,79	5,78	1,4*(22+b)/e, max ↓ 2,64
		M	3,19	6,6	1,6*(22+b)/e, max ↓ 3,02
		S	3,59	7,43	1,8*(22+b)/e, max ↓ 3,39
		I	4,39	9,08	2,2*(22+b)/e, max ↓ 4,15
Characteristic values, b and e in mm			3,98	8,25	2,0*(22+b)/e, max ↓ 3,77

**2 angle brackets V14, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	34	P	4,79	8,48	$2,4 \cdot (20+b)/e$ , max ↓ 4,52
		L	5,59	9,89	$2,8 \cdot (20+b)/e$ , max ↓ 5,28
		M	6,38	11,30	$3,2 \cdot (20+b)/e$ , max ↓ 6,03
		S	7,18	12,72	$3,6 \cdot (20+b)/e$ , max ↓ 6,79
		I	8,78	15,54	$4,4 \cdot (20+b)/e$ , max ↓ 8,29
Characteristic values, b and e in mm			7,98	14,13	$4,0 \cdot (20+b)/e$ , max ↓ 7,54

**2 angle brackets V15, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	24	P	1,60	2,57	$1,45 \cdot (42,9+b)/e$ , max ↓ 4,52
		L	1,86	3,00	$1,69 \cdot (42,9+b)/e$ , max ↓ 5,28
		M	2,13	3,42	$1,93 \cdot (42,9+b)/e$ , max ↓ 6,03
		S	2,39	3,85	$2,17 \cdot (42,9+b)/e$ , max ↓ 6,79
		I	2,93	4,71	$2,65 \cdot (42,9+b)/e$ , max ↓ 8,29
Characteristic values, b and e in mm			2,67	4,28	$2,41 \cdot (42,9+b)/e$ , max ↓ 7,54

**1 angle bracket V20, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2/F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	4 nails	P	1,56	1,63	$15,6/e$ , max ↓ 7,83	1,09
		L	1,56	1,90	$15,6/e$ , max ↓ 9,14	1,09
		M	1,56	2,18	$15,6/e$ , max ↓ 10,44	1,09
Hole marked yellow	1 bolt	S	1,56	2,45	$15,6/e$ , max ↓ 10,69	1,09
		I	1,56	2,99	$15,6/e$ , max ↓ 10,69	1,09
Characteristic values, b and e in mm			1,56	2,72	$15,6/e$ , max ↓ 13,05	1,09

**2 angle brackets V20, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	8 nails	P	3,12	3,27	7,83
		L	3,12	3,82	9,14
		M	3,12	4,36	10,44
Holes marked yellow	2 bolts	S	3,12	4,91	10,69
		I	3,12	6,00	10,69
Characteristic values			3,12	5,45	13,05

**1 angle bracket V21, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	8 nails	P	1,23	1,47	20,5/e, max ↓ 19,8	10,69*b/e, max ↓ 1,31
		L	1,23	1,72	20,5/e, max ↓ 19,8	12,47*b/e, max ↓ 1,31
		M	1,23	1,96	20,5/e, max ↓ 19,8	14,25*b/e, max ↓ 1,31
Hole marked yellow	1 bolts	S	1,23	2,21	20,5/e, max ↓ 19,8	16,03*b/e, max ↓ 1,31
		I	1,23	2,70	20,5/e, max ↓ 19,8	19,59*b/e, max ↓ 1,31
Characteristic values, b and e in mm			1,23	2,45	20,5/e, max ↓ 19,8	17,82*b/e, max ↓ 1,31

**2 angle brackets V21, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	16 nails	P	2,47	2,94	14,64
		L	2,47	3,43	17,08
		M	2,47	3,92	19,52
Holes marked yellow	2 bolts	S	2,47	4,41	19,80
		I	2,47	5,39	19,80
Characteristic values			2,47	4,90	19,80

**1 angle bracket V21, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	12	P	0,88	1,47	22,5/e, max ↓ 2,14	10,69*b/e, max ↓ 1,31
		L	1,02	1,72	22,5/e, max ↓ 2,49	12,47*b/e, max ↓ 1,31
		M	1,17	1,96	22,5/e, max ↓ 2,85	14,25*b/e, max ↓ 1,31
		S	1,31	2,21	22,5/e, max ↓ 3,20	16,03*b/e, max ↓ 1,31
		I	1,61	2,70	22,5/e, max ↓ 3,92	19,59*b/e, max ↓ 1,31
Characteristic values, b and e in mm			1,46	2,45	22,5/e, max ↓ 3,56	17,82*b/e, max ↓ 1,31

**1 angle bracket V170, beam to concrete connection**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	16 nails	P	18,02	4,45	19,79	2,47
		L	21,02	5,19	23,09	2,88
		M	24,02	5,94	26,39	3,29
Holes marked yellow	4 bolt	S	27,03	6,68	29,69	3,70
		I	33,03	8,16	36,29	4,52
Characteristic values, b and e in mm			30,03	7,42	32,99	4,11

**2 angle brackets V170, beam to concrete connection**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	32 nails	P	36,04	8,90	18,02*b/e, max ↓ 19,79
		L	42,04	10,39	21,02*b/e max ↓ 23,09
		M	48,05	11,87	24,02*b/e max ↓ 26,39
Holes marked yellow	8 bolts	S	54,05	13,36	27,03*b/e max ↓ 29,69
		I	66,07	16,32	33,03*b/e max ↓ 36,29
Characteristic values			60,06	14,84	30,03*b/e max ↓ 32,99

**1 angle bracket V170, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	16 nails	P	3,70	4,45	9,01	2,47
		L	4,31	5,19	10,51	2,88
		M	4,93	5,94	12,02	3,29
	10 nails	S	5,54	6,68	13,52	3,70
		I	6,78	8,16	16,52	4,52
Characteristic values, b and e in mm			6,16	7,42	15,02	4,11

**2 angle brackets V170, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	32 nails	P	7,39	8,90	$3,70 \cdot (31+b)/e$ max ↓ 9,01
		L	8,62	10,39	$4,31 \cdot (31+b)/e$ max ↓ 10,51
		M	9,86	11,87	$4,93 \cdot (31+b)/e$ max ↓ 12,02
	20 nails	S	11,09	13,36	$5,54 \cdot (31+b)/e$ max ↓ 13,52
		I	13,55	16,32	$6,78 \cdot (31+b)/e$ max ↓ 16,52
Characteristic values, b and e in mm			12,32	14,84	$6,16 \cdot (31+b)/e$ max ↓ 15,02

**1 angle bracket P4, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2/F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	4 nails	P	2,25	1,19	$22,5/e$ , max ↓ 8,11	$5,35 \cdot b/e$ , max ↓ 1,03
		L	2,25	1,39	$22,5/e$ , max ↓ 9,46	$6,24 \cdot b/e$ , max ↓ 1,20
		M	2,25	1,58	$22,5/e$ , max ↓ 9,90	$7,13 \cdot b/e$ , max ↓ 1,38
Hole marked yellow	1 bolt	S	2,25	1,78	$22,5/e$ , max ↓ 9,90	$8,02 \cdot b/e$ , max ↓ 1,55
		I	2,25	2,18	$22,5/e$ , max ↓ 9,90	$9,80 \cdot b/e$ , max ↓ 1,89
Characteristic values, b and e in mm			2,25	1,98	$22,5/e$ , max ↓ 9,90	$8,91 \cdot b/e$ , max ↓ 1,72



**2 angle brackets P4, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	8 nails	P	4,5	2,38	9,9
		L	4,5	2,77	9,9
		M	4,5	3,17	9,9
Holes marked yellow	2 bolts	S	4,5	3,56	9,9
		I	4,5	4,36	9,9
Characteristic values			4,5	3,97	9,9

**1 angle bracket P4, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4, [kN]	F5, [kN]
Holes marked blue	4	P	0,88	1,19	22,5/e, max ↓ 2,14	5,35*b/e, max ↓ 1,21
		L	1,02	1,39	22,5/e, max ↓ 2,49	6,24*b/e, max ↓ 1,41
		M	1,17	1,58	22,5/e, max ↓ 2,85	7,13*b/e, max ↓ 1,61
		S	1,31	1,78	22,5/e, max ↓ 3,20	8,02*b/e, max ↓ 1,81
		I	1,61	2,18	22,5/e, max ↓ 3,92	9,80*b/e, max ↓ 2,21
Characteristic values, b and e in mm			1,46	1,98	22,5/e, max ↓ 3,56	8,91*b/e, max ↓ 2,02

**2 angle brackets K4, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	34 nails	P	5,16	6,41	6,79
		L	6,02	7,48	7,92
		M	6,88	8,55	9,05
		S	7,74	9,62	10,18
		I	9,46	11,76	12,44
Characteristic values			8,60	10,69	11,31

**1 angle bracket 1-150, wood to concrete**

Expansion bolt	No. of bolts pr connection	Load Duration	F1, [kN]
Holes marked yellow	1 bolt	P	4,12
		L	4,80
		M	5,49
	1 bolt	S	6,17
		I	7,55
Characteristic values			6,86

**2 angle brackets LV1, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F1, [kN]	F2 /F3, [kN]	F4 /F5, [kN]
Holes marked blue	20 nails	P	1,89	1,30	$1,44 \cdot (20,7+b)/e$ , max ↓ 4,52
		L	2,20	1,51	$1,68 \cdot (20,7+b)/e$ , max ↓ 5,28
		M	2,52	1,73	$1,92 \cdot (20,7+b)/e$ , max ↓ 6,03
		S	2,83	1,94	$2,16 \cdot (20,7+b)/e$ , max ↓ 6,79
		I	3,46	2,38	$2,64 \cdot (20,7+b)/e$ , max ↓ 8,29
Characteristic values, b and e in mm			3,15	2,16	$2,40 \cdot (20,7+b)/e$ , max ↓ 7,53

**Angle Bracket V26, V27**  
**Design Basis**




Figure 4. Force, 1 or 2 brackets, wood to concrete  
 $F_n$




Figure 5. Example of washer, 40 x 50 x 10 mm

It must be checked that the bolts used have the necessary strength. Angle brackets with same dimensions where only the length is different may also use these values.

Fastening with bolts and nails:

$F$  With the use of a washer with a thickness of 10 mm or more and n number of nails

Fastening with nails:

$F_n$  Angle without the use of a washer and mounted with nails in wood

The values have been assessed in accordance with EC 5 Table 3.1- "Values of  $K_{mod}$ " where needed

**1 angle bracket V26 – V27, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	$F$ , [kN]
Nailing holes	n number of nails	P	1,13*n, max ↑ 17,82
		L	1,32*n, max ↑ 17,82
		M	1,50*n, max ↑ 17,82
Hole marked yellow	1 bolt	S	1,69*n, max ↑ 17,82
		I	2,07*n, max ↑ 17,82
Characteristic values			1,88*n, max ↑ 17,82

**2 angle brackets V26 – V27, wood to concrete**

Paslode Connector nails 4,0 × 40 mm / Expansion bolt	No. of fasteners pr connection	Load Duration	F, [kN]
Nailing holes	n number of nails	P	2,25*n, max ↑ 35,64
		L	2,63*n, max ↑ 35,64
		M	3,00*n, max ↑ 35,64
Holes marked yellow	2 bolts	S	3,38*n, max ↑ 35,64
		I	4,13*n, max ↑ 35,64
Characteristic values			3,75*n, max ↑ 35,64

**1 angle bracket V26 – V27, wood to wood**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F <sub>n</sub> , [kN]
Nailing holes	n number of nails	P	1,13*n, max ↑ 1,23
		L	1,32*n, max ↑ 1,44
		M	1,50*n, max ↑ 1,64
Hole marked blue	4 nails	S	1,69*n, max ↑ 1,85
		I	2,07*n, max ↑ 2,26
Characteristic values			1,88*n, max ↑ 2,05

**2 angle brackets V26 – V27, wood to wood**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F <sub>n</sub> , [kN]
Nailing holes	n number of nails	P	2,25*n, max ↑ 2,47
		L	2,63*n, max ↑ 2,88
		M	3,00*n, max ↑ 3,29
Holes marked blue	8 nails	S	3,38*n, max ↑ 3,70
		I	4,13*n, max ↑ 4,52
Characteristic values			3,75*n, max ↑ 4,11

**Angle Bracket P1-8, P1-10, P1-12, P2-10, P2-12**  
**Design Basis**




Figure 6. Force, 1 bracket wood to wood, beam to beam

**One angle bracket per connection**

F Lateral force acting in the beam direction perpendicular to the vertical flap directed towards the angle brackets vertical flap.

The values have been assessed in accordance with EC 5 Table 3.1- "Values of  $K_{mod}$ "

**Wane**

For F wane is allowed on the side towards the angle bracket with an extent from the bottom to the lower row of nails. For all other forces wane is not allowed under the angle bracket.

**1 angle bracket P1-8, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F, [kN]
Holes marked blue	9	P	2,26
		L	2,64
		M	3,02
		S	3,39
		I	4,15
Characteristic values			3,77

**1 angle bracket P1-10, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F, [kN]
Holes marked blue	9	P	4,52
		L	5,28
		M	6,03
		S	6,79
		I	8,29
Characteristic values			7,54

**1 angle bracket P1-12, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F, [kN]
Holes marked blue	9	P	4,52
		L	5,28
		M	6,03
		S	6,79
		I	8,29
Characteristic values			7,54

**1 angle bracket P2-10, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F, [kN]
Holes marked blue	9	P	4,52
		L	5,28
		M	6,03
		S	6,79
		I	8,29
Characteristic values			7,54

**1 angle bracket P2-12, beam to beam connection**

Paslode Connector nails 4,0 × 40 mm	No. of nails pr connection	Load Duration	F, [kN]
Holes marked blue	9	P	4,52
		L	5,28
		M	6,03
		S	6,79
		I	8,29
Characteristic values			7,54