tesa® Professional 4334 Precision Mask®



Product Information

Malertape av høy kvalitet for nøyaktige og flate malingskanter

Produktbeskrivelse

tesa® Precision Mask® 4334 gir lynskarpe malingskanter og er samtidig ekstremt enkel i bruk - takket være den ideelle kombinasjonen av den spesielt smidige baksiden og den perfekt komponerte akrylklebemassen. Dette hjelper tapen å klebe ekstremt tett til overflaten og dermed hindre malingstårer. Kombinasjonen av profesjonell malingstape og din ekspertise vil gi malearbeid som gjør dine kunder fornøyde. I tillegg vil malingstapens høye kvalitet spare deg for kostbart retusjeringsarbeid.

Funksjoner

- Innendørs maskering (opptil 6 måneder)
- Utendørs maskering (opp til 8 uker)
- For glatte og lett strukturerte overflater
- For male- og lakkeringsarbeid av høy kvalitet
- For spraymaling med påfølgende ovnstørking opp til 120° C/30 min

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

• Bæremateriale	Washi paper	• Total tykkelse	90 µm
• Klebetype	Akryl		

Egenskaper / ytelsesverdier

• UV resistance	8 uke/r	• Bruddstyrke	30 N/cm
• Bruddforlengelse	4 %	• Hand tearability	very good

Klebekraft

• Klebeevne på Stål	1.8 N/cm

For latest information on this product please visit http://l.tesa.com/?mp=04334

tesa® Professional 4334 Precision Mask®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?mp=04334