

Saint-Gobain API BV  
Newtonweg 1  
3846 BJ Harderwijk  
The Netherlands

P.O. Box 1  
3840 AA Harderwijk  
The Netherlands  
T +31 (0)341 474600  
F +31 (0)341 474626  
E [sales@api.nl](mailto:sales@api.nl)  
[www.api.nl](http://www.api.nl)

Chamber of Commerce  
08015950  
BTW NL004318894.B.01

## Declaration of Performance 0007-180E

### Quick-Lock wall connections


1. Unique identification of product : Quick-Lock®wallconnections
2. Identification of the construction product components:  
Quick-Lock wall angle 19-19/24/32, 24-24/32, U-38, 24-12-12-24, 15-18-15-25, 15-6-15-27, 20-30, F-section 27-41-13, clamping edge profile 6.
3. Intended use: Suspension system components for ceilings in building interiors
4. Manufacturer: Saint-Gobain API BV Newtonweg 1 Harderwijk The Netherlands [www.api.nl](http://www.api.nl)
5. Authorized representatives: n.a.
6. System of assessment and verification of performance:
  - 6.1. Loadbearing capacity: System 3
  - 6.2. Reaction to fire: System 3 or 4
  - 6.3. Durability: System 4
7. Harmonized standard covering the construction product- EN 13964-2007 suspended ceilings:
  - 7.1. Loadbearing capacity: Tests carried out by NB0432 MPA Dortmund; NB1153 TNO Delft
  - 7.2. Reaction to fire: Galvanized steel Commission decision 96/603/EC; Coil-coated steel Commission decision 2010/737/EC: Tests carried out by NB 0679 CSTB RA08-0251,
  - 7.3. Durability: EN 13964 Table 8
8. European Technical Assessment: n.a.

### 9. Declared performances:

	7.1 Load bearing capacity					7.2 Reaction to fire	7.3 Durability
		Fixation distance mm	F <sub>ef</sub> 0,8mm N	F <sub>ef</sub> 4mm N	Notified body		
Wallangle 19-19		250	npd	npd		Class A1	Class B
Wallangle 19-24		250	39,0	154,0	NB1153	Class A1	Class B
Wallangle 19-24 alu		250	39,0	154,0		Class A1	Class B
Wallangle 24-24		250	39,0	154,0		Class A1	Class B
Wallangle 19-32		250	39,0	154,0		Class A1	Class B
Wallangle 24-32		250	39,0	154,0		Class A1	Class B
Wallangle U-38		250	39,0	154,0		Class A1	Class B
Wallangle 24-12-12-24		250	39,0	154,0		Class A1	Class B
Clamping edgeprofile 6		250	39,0	154,0		Class A1	Class B
F-section 27-41-13		n.a.	n.a.	n.a.		Class A1	Class B
Wallangle 15-8-15-25		250	39,0	154,0		Class A1	Class B
Wallangle 15-6-15-27		250	39,0	154,0		Class A1	Class B
Wallangle heavy 20-30		250	149,0	624,0	NB1153	Class A1	Class B

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performances point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for on behalf of the manufacturer:



J. van Eekhout  
Managing Director  
Harderwijk NL 21-05-2013

# QUICK-LOCK®

## Ceiling systems

