## **Declaration of Performance**

Nr.: 15651-0565-1-UK

1. Unique identification of product type:

ETAG 026 part 1 & 2

2. Identification of construstion product:

Fire Guard A 565

Batch number: See product packaging

3. Intended use of product:

Sealant for use in linear joint seals complying with the contents of ETA 14/0110

4. Adress and name of the producer:

Dana Lim A/S, Københavnsvej 220, 4600 Køge, Danmark

5. Name and adress of authorized representative:

Not relevant

6. System and verification of consistency of the construction product (Annex V):

**AVCP System 1** 

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

Not Relevant

8. In case of declaration of performance concerning a construction product covered by a European Technical Assessment has been issued:

Warrington Certification Limited issued European Technical Approval –
ETA 14/0110 on the basis of ETAG 026 part 1 General fire protection products & ETAG 026 part 2 fire stopping and fire sealing products & issued certificate of conformity 1121-CPR-JA5029



9. Declared Performance:

Declared Performa	rice.		
ETAG Clause N°	Essential Characteristics	Assessment of Characteristic	Technical Specification
Safety in case of fire		Characteristic	Specification
2.4.1	Reaction to fire	Class F	EN13501-1
2.4.2	Resistance to fire	Resistance to fire performance & field of application in accordance with EN13051-2 See ETA 14/0055 clause 3.2 - Annex C	EN1366-3:2009 EN13501-2 as given in Annex C
Hygiene, Health and	Environment		
2.4.3	Air Permeability	Air Permeability See clause 3.3 ETA14/0110: 600Pa	EN 1026:2000
2.4.9	Airborne Sound Insulation	See ETA 14/0110 Clause 3.9 – Rw (C;Ctr) = 38 (G;-2) dB	EN ISO 10140- 2:2010
2.4.5	Dangerous Substances	See ETA 14/0110 Clause 3.5	
Energy, Economy an	d heat retention		
2.4.12	Service & Durability	Z1 (0/+40c) intended for use at internal conditions with high humidity (85%) in accordance with EOTA technical documents TR024, Clause 3.12	
	Movement cabability	12.5P	According to ISO 11600 - F

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Køge, 06.02.2015

Kenneth Holm Andersen Chemical Engineer

