

MULTI/JOINT® 3057 Plus Wide Range Flange adaptor, restraint, Uni/Fiksers

Model:


- Suitable for all kinds of pipe material
- Suitable for water and gas
- Ductile cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information
- Hygiene protection included DN50 - DN600

DN (mm)	Range 1 (mm)	Flange 3 (mm)	Drilling pat- tern	NBR / A2 Code	EPDM / A2 Code	Weight (kg)
50	46 - 71	50	PN16	709 355 210	709 355 610	5.600
65	63 - 90	60/65	PN16	709 355 212	709 355 612	6.500
80	84 - 105	80	PN16	709 355 214	709 355 614	6.500
100	104 - 132	100	PN16	709 355 216	709 355 616	8.600
125	132 - 155	125	PN16	709 355 218	709 355 618	13.000
150	154 - 192	150	PN16	709 355 220	709 355 620	14.000
200	192 - 232	200	PN10	709 355 224	709 355 624	21.700
200	192 - 232	200	PN16	709 355 225	709 355 625	21.700
250	267 - 310	250	PN10	709 355 228	709 355 628	31.100
250	267 - 310	250	PN16	709 355 229	709 355 629	31.100
300	315 - 356	300	PN10	709 355 232	709 355 632	40.500
300	315 - 356	300	PN16	709 355 233	709 355 633	40.500
350	352 - 393	350	PN10	709 355 236	709 355 636	52.100
350	352 - 393	350	PN16	709 355 237	709 355 637	52.100
400	392 - 433	400	PN10	709 355 238	709 355 638	65.100
400	392 - 433	400	PN16	709 355 239	709 355 639	65.100
500	500 - 532	500	PN10/PN16	709 355 274	709 355 674	89.000
600	605 - 637	600	PN10/PN16	709 355 278	709 355 678	118.100

DN (mm)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
50	709 355 010	709 355 310	5.600
65	709 355 012	709 355 312	6.500
80	709 355 014	709 355 314	6.500
100	709 355 016	709 355 316	8.600
125	709 355 018	709 355 318	13.000
150	709 355 020	709 355 320	14.000
200	709 355 024	709 355 324	21.700
200	709 355 025	709 355 325	21.700
250	709 355 028	709 355 328	31.100
250	709 355 029	709 355 329	31.100
300	709 355 032	709 355 332	40.500
300	709 355 033	709 355 333	40.500
350	709 355 036	709 355 336	52.100
350	709 355 037	709 355 337	52.100
400	709 355 038	709 355 338	65.100
400	709 355 039	709 355 339	65.100
500	709 355 074	709 355 374	89.000
600	709 355 078	709 355 378	118.100

Data sheet

valid from: 4/12/18



DN (mm)	a (mm)	b (mm)	d (mm)	e (mm)	PN Water (bar)	PN Gas (bar)	No. of bolt holes flange
50	179 - 194	164	100	3xM12	16.0	8	4
65	187 - 198	186	95	3xM12	16.0	8	4
80	183 - 197	204	115	3xM12	16.0	8	8
100	181 - 200	236	110	3xM16	16.0	8	8
125	196 - 214	264	120	4xM16	16.0	8	8
150	194 - 222	304	120	4xM16	16.0	8	8
200	224 - 251	354	140	6xM16	16.0	8	8
200	224 - 251	354	140	6xM16	16.0	8	12
250	260 - 295	432	170	6xM20	16.0	8	12
250	260 - 295	432	170	6xM20	16.0	8	12
300	283 - 318	490	170	8xM20	16.0	8	12
300	283 - 318	490	170	8xM20	16.0	8	12
350	326 - 364	534	245	8xM20	10.0	5	16
350	326 - 364	534	245	8xM20	10.0	5	16
400	356 - 395	574	275	10xM20	10.0	5	16
400	356 - 395	574	275	10xM20	10.0	5	16
500	365 - 390	715	275	10xM20	10.0	5	20
600	365 - 390	840	275	14xM20	10.0	5	20

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>