

## MULTI/JOINT® 3057 Plus Wide Range Flange adaptor, restraint, Uni/Fiksers

### Model:


- Suitable for all kinds of pipe material
- Suitable for water and gas
- Ductile cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information
- Hygiene protection included DN50 - DN600

DN (mm)	Range 1 (mm)	Flange 3 (mm)	Drilling pat- tern	NBR / A2 Code	EPDM / A2 Code	Weight (kg)
50	46 - 71	50	PN16	<b>709 355 210</b>	<b>709 355 610</b>	5.600
65	63 - 90	60/65	PN16	<b>709 355 212</b>	<b>709 355 612</b>	6.500
80	84 - 105	80	PN16	<b>709 355 214</b>	<b>709 355 614</b>	6.500
100	104 - 132	100	PN16	<b>709 355 216</b>	<b>709 355 616</b>	8.600
125	132 - 155	125	PN16	<b>709 355 218</b>	<b>709 355 618</b>	13.000
150	154 - 192	150	PN16	<b>709 355 220</b>	<b>709 355 620</b>	14.000
200	192 - 232	200	PN10	<b>709 355 224</b>	<b>709 355 624</b>	21.700
200	192 - 232	200	PN16	<b>709 355 225</b>	<b>709 355 625</b>	21.700
250	267 - 310	250	PN10	<b>709 355 228</b>	<b>709 355 628</b>	31.100
250	267 - 310	250	PN16	<b>709 355 229</b>	<b>709 355 629</b>	31.100
300	315 - 356	300	PN10	<b>709 355 232</b>	<b>709 355 632</b>	40.500
300	315 - 356	300	PN16	<b>709 355 233</b>	<b>709 355 633</b>	40.500
350	352 - 393	350	PN10	<b>709 355 236</b>	<b>709 355 636</b>	52.100
350	352 - 393	350	PN16	<b>709 355 237</b>	<b>709 355 637</b>	52.100
400	392 - 433	400	PN10	<b>709 355 238</b>	<b>709 355 638</b>	65.100
400	392 - 433	400	PN16	<b>709 355 239</b>	<b>709 355 639</b>	65.100
500	500 - 532	500	PN10/PN16	<b>709 355 274</b>	<b>709 355 674</b>	89.000
600	605 - 637	600	PN10/PN16	<b>709 355 278</b>	<b>709 355 678</b>	118.100

DN (mm)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
50	<b>709 355 010</b>	<b>709 355 310</b>	5.600
65	<b>709 355 012</b>	<b>709 355 312</b>	6.500
80	<b>709 355 014</b>	<b>709 355 314</b>	6.500
100	<b>709 355 016</b>	<b>709 355 316</b>	8.600
125	<b>709 355 018</b>	<b>709 355 318</b>	13.000
150	<b>709 355 020</b>	<b>709 355 320</b>	14.000
200	<b>709 355 024</b>	<b>709 355 324</b>	21.700
200	<b>709 355 025</b>	<b>709 355 325</b>	21.700
250	<b>709 355 028</b>	<b>709 355 328</b>	31.100
250	<b>709 355 029</b>	<b>709 355 329</b>	31.100
300	<b>709 355 032</b>	<b>709 355 332</b>	40.500
300	<b>709 355 033</b>	<b>709 355 333</b>	40.500
350	<b>709 355 036</b>	<b>709 355 336</b>	52.100
350	<b>709 355 037</b>	<b>709 355 337</b>	52.100
400	<b>709 355 038</b>	<b>709 355 338</b>	65.100
400	<b>709 355 039</b>	<b>709 355 339</b>	65.100
500	<b>709 355 074</b>	<b>709 355 374</b>	89.000
600	<b>709 355 078</b>	<b>709 355 378</b>	118.100

# Data sheet

valid from: 4/12/18



DN (mm)	a (mm)	b (mm)	d (mm)	e (mm)	PN Water (bar)	PN Gas (bar)	No. of bolt holes flange
50	179 - 194	164	100	3xM12	16.0	8	4
65	187 - 198	186	95	3xM12	16.0	8	4
80	183 - 197	204	115	3xM12	16.0	8	8
100	181 - 200	236	110	3xM16	16.0	8	8
125	196 - 214	264	120	4xM16	16.0	8	8
150	194 - 222	304	120	4xM16	16.0	8	8
200	224 - 251	354	140	6xM16	16.0	8	8
200	224 - 251	354	140	6xM16	16.0	8	12
250	260 - 295	432	170	6xM20	16.0	8	12
250	260 - 295	432	170	6xM20	16.0	8	12
300	283 - 318	490	170	8xM20	16.0	8	12
300	283 - 318	490	170	8xM20	16.0	8	12
350	326 - 364	534	245	8xM20	10.0	5	16
350	326 - 364	534	245	8xM20	10.0	5	16
400	356 - 395	574	275	10xM20	10.0	5	16
400	356 - 395	574	275	10xM20	10.0	5	16
500	365 - 390	715	275	10xM20	10.0	5	20
600	365 - 390	840	275	14xM20	10.0	5	20

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>