

Leica Lino

One of the industry's most versatile and precise line and point lasers that can adapt to any scenario





Our unique technologies

Technology from Leica Geosystems



Outstanding visibility

All Leica Lino products incorporate decades of knowledge and experience in the fields of optics and electronics. The results are outstanding visibility and high accuracy of our red and green lasers.

Li-lon

Li-ion batteries can run a Lino for up to 44 hours on a single charge (depending on the model). In addition, the Lino tri-power concept offers run/charge capability along with an alkaline battery backup tray to keep you going.





Ruggedness

Leica Lino products are well crafted with high quality materials, therefore perfectly suited for construction sites. Each product is fully tested to meet Leica Geosystems quality standards.

Magnetic adapters

The Leica Lino products can easily be connected to precision engineered adapters via strong magnets, allowing you to easily position it for any possible measuring scenario.






EXPLORE >

The Lino L2 cross-line laser projects sharp lines at the correct angles to one another. The increased laser power enhances line visibility and improves the efficiency of interior work

- Self-Leveling
- Range: 82' with receiver 262'
- Visibility: up to 4 times better than DIY line lasers



Reliable, Quick Layouts

Easy to setup: self-leveling with

sharp, bright, visible lines



Works For All Applications

Drywall, partitions, ceilings,
flooring and millwork with a full

line of accessories and adapters



Cost Effective Solutions

Included Li-lon battery works for 44 hrs, saving \$360/yr in disposable batteries

Replaceable glass lens saves buying a replacement unit saving \$300

Pro-Kit

- Lino L2 Laser Layout Tool
- Molded Case
- Twist 250
- Target Plate
- Li-Ion Battery / Charger
- AA Battery Tray

Technical Data

Accuracy, Typical ±0.08" @ 33'

Range 82'

Range w/ Receiver 282'

Laser Type Class 2 635nm

Laser Output Power 30mW

Visibility 0.2 Spectral Efficiency

Beam Direction vertical, horizontal

Leveling System automatic pendulum lockable

Tripod Thread 1/4", 5/8"

Battery Runtime Up to 44hrs of operation

Batteries 3.6V/18.7Wh Li-lon included or type AA,

3 x 1.5 V

Protection Class IP54

Dimensions 2.5 x 3.9 x 4.3 in

See Full Specs >

Layout Accessories

- DISTO D2
- DISTO E7500i
- DISTO S910
- DISTO Plan

View Video Here >

Lino Adapters

- Twist 360
- Twist 250
- Clamp 290
- Receiver RGR 200
- Wall Mount UAL 130

View Video Here >



Our dedication to quality assures that the products we deliver are of best quality. And with extensive lab testing, you can rest assured that your device is of highest durability.