	contains	m²	ft²	weight
1 pack cadenza	9 planks	2,66 m ²	28.67 ft ²	19,4 kg
1 pallet cadenza	56 packs	149,16 m²	1605.60 ft ²	1098 kg

product specifications

dimensions mm / inch	1383 x 214 mm / 54.45" x 8.43"
total thickness mm / inch	8 mm/ 0.31"
bevels	4
loc system	duoloc
level of use according to European standard EN10874	23 heavy domestic use
	32 general commercial use
residential warranty	20 years
commercial warranty	3 years

composition

surface layer	direct laminated paper, impregnated with melamine resin	
substrate	moisture resistant High Density Fiberboard (HDF)	
backing	direct laminated paper, impregnated with melamine resin	

test results

abrasion resistance	EN13329	AC4 (IP≤4000)	
impact resistance	EN13329	Small ball : ≤ 12 N - Big ball : ≤ 750 mm	
thickness swelling	EN13329	≤ 18%	
fire resistance	EN14041	Cfl-S1	
formaldehyde emission	EN14041	E1	
slip resistance	EN14041	DS	
density	EN323	900 kg/m³	
resistance to staining	EN438	5 (groups 1+2); 4 (group 3)	
effect of a furniture leg	EN424	no damage (foot type 0)	
effect of a castor chair	EN425	no change in appearance or damage	
thermal resistance in combination with underlay Excellence Plus	ISO 8302	0,08 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com	









product leaflet installation manual warranty conditions care&maintenance floor heating manual underlay guide

