GALVACOLOR

Reference : 10678-10725

1. General description

Zinc-phosphate protective coating. Ideal for identification of utility conduits. Primer and topcoat in one. Short drying time. Official RAL identification colors. Conform the protect category C3(ISO 12944-2).



2. Features

- No chlorinated solvents.
- Totally free of lead and chromates.
- Protects metals and alloys.
- ISO 12944-2 protect category C3

3. Applications

- Long term corrosion protection.

4. Directions

- Shake until the agitator ball moves freely in the can.
- Use only with adequate ventilation.
- Remove most of the loose dirt with a wire brush.
- Minimum application temperature = 10 °C
- Apply to a clean, dry surface.
- Spray from a distance of approximately 20 - 30 cm.
- Apply a thin even film.
- Best results are obtained with 2 lighter rather than 1 heavy coat. Additional coats can be applied after 15 - 20 minutes.
- Clean the aerosol valve by turning the can upside down and spraying until only propellant escapes.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

Source NOBB, 3/9/2025

GALVACOLOR

Reference : 10678-10725

Appearance	Liquid.
Density	1.08 g/cm3 (@ 20°C).
Flash Point	15 °C (Closed Cup)
Drying time active product	30µm = 20 min
salt spray resistance active product	> 240 h
Typical coat weight	30 µm

6. Packaging

Aerosol 12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-GALVACOLOR-20100518

Date 18/05/2010

Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com