

Robust™ Flislim - Lett

Batch number see side sack print

Declaration of performance

Labelling of declaration of performance and clear identification code of the product type
110333-01-EN12004-C2-TE-S1

Intended use

Lightweight, highly flexible thin-bed adhesive with extremely high adhesive strength. 35% higher yield. For walls and floors, indoors and outdoors.

Manufacturer

Steinhardt AS • Postboks 8627 Ranheim • 7452 Trondheim, Norway

System for assessment and verification of constancy of performance

System 4 in case of reaction to fire and System 3 for the other essential characteristics

Notified testing body

Materialprüfungsamt Nordrhein-Westfalen e.V. (MPA NRW) – Kennnummer 0432

has carried out the initial test of the product with regard to the essential characteristics (except reaction to fire) of system 3 and issued the following:

Harmonised standard

EN 12004 :2012

Declared performance

Essential characteristics	Performance
Reaction to fire	E
Bond strength	Tensile adhesion strength after dry storage $\geq 1,00$ N/mm ²
Durability against exposure to climate/heat storage	Tensile adhesion strength after warm storage $\geq 1,00$ N/mm ²
Durability against exposure to climate/heat storage	Tensile adhesion strength after water storage $\geq 1,00$ N/mm ²
Durability against exposure to freeze/thaw storage	Tensile adhesion strength after freeze/thaw storage $\geq 1,00$ N/mm ²
Release of dangerous substances	NPD

The performance of the product conforms with the declared performance. The manufacturer is solely responsible for compiling this declaration of performance which is consistent with the regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer of:



Stian Schevig. Daglig leder, Steinhardt AS.
Date of issue. 01.06.2016.