



RAPIDTRAK[®]

SERIES



1 YEAR
LTD. COMMERCIAL
WARRANTY

3 YEAR
LTD. RESIDENTIAL
WARRANTY

GAIN TRACTION NO MATTER WHAT MOTHER NATURE THROWS AT YOU WITH THE VERSATILITY OF A WHEEL OR TRACK UNIT IN A SINGLE MACHINE.

RapidTrak[®] delivers unrivalled power under any conditions. The Intuitive, user-friendly design allows operators to switch between wheel and track settings in seconds. RapidTrak maintains traction even against high snow piles on hilly or slippery pavement, and a wheeled setting provides quick, effortless manoeuvrability on flat surfaces.

SPEED AND TRACTION

Ariens[®] RapidTrak[®] combines track-system stability with the speed of a wheel driven Sno-Thro[®].

MAXIMUM MANOEUVRABILITY

Adjust on the go by moving the back wheel up to turn with the ease of a wheeled Sno-Thro.

UNDISPUTED POWER

The dual-belt auger drive system delivers maximum torque quickly, so you can power through piles of snow.

PRODUCT SPECIFICATIONS

	RAPIDTRAK	RAPIDTRAK	RAPIDTRAK
DESIGNATION	COMPACT 24RT	DELUXE 28RT	PLATINUM 28RT
MODEL #	920330	921330	921335
STAGE TYPE	TWO STAGE	TWO STAGE	TWO STAGE
ENGINE POWER	208 CC (12.8NM)	291CC (19.5NM)	369CC EFI (23.1NM)
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX
STARTING SYSTEM	230V/RECOIL	230V/RECOIL	230V RECOIL
CLEARING WIDTH	24 IN (60.1 CM)	28 IN (71.2 CM)	28 IN (71.2 CM)
HOUSING HEIGHT	20 IN (50.8 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)
THROWING DISTANCE	3 - 40 FT (0.9 - 12.2 M)	3 - 50 FT (0.9 - 15.2 M)	3 - 55 FT (0.9 - 16.7 M)
CHUTE TURNING RADIUS	205°	200°	200°
CHUTE ROTATION	2.5X ICE DRILL	2.5X ICE DRILL	2.5X ICE DRILL
DEFLECTOR CONTROL	REMOTE	REMOTE	REMOTE
TYRE SIZE	5.5 IN (14 CM) WIDE TRACK	5.5 IN (14 CM) WIDE TRACK	5.5 IN (14 CM) WIDE TRACK
TYRE TYPE	DIRECTIONAL SNOW TRACK	DIRECTIONAL SNOW TRACK	DIRECTIONAL SNOW TRACK
STEERING	SOLID LOCKED	AUTO-TURN	AUTO-TURN
DRIVE TYPE	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC
SPEEDS	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE
GEAR CASE	CAST IRON	CAST IRON	CAST IRON
GEAR CASE WARRANTY	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	12 IN (30.5 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER DIAMETER	11 IN (27.9 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER TYPE	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED
SKID SHOES	STEEL REVERSIBLE	STEEL REVERSIBLE	POLY SKID REVERSIBLE
SCRAPER BAR	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 1YR COMM
LENGTH	53.3 IN (135.4 CM)	58.6 IN (148.8 CM)	60.3 IN (153.2 CM)
WIDTH	26.4 IN (67.1 CM)	29.9 IN (75.9 CM)	30.2 IN (76.7 CM)
HEIGHT	43.4 IN (110.2 CM)	45.3 IN (115.1 CM)	46.6 IN (118.4 CM)
WEIGHT	220 LBS (99.8 KG)	283.1 LBS (128.4 KG)	331 LBS (150.1 KG)
ACCESSORIES AT A GLANCE	HANDWARMER KIT, DRIFT CUTTER KIT, FRONT WEIGHT KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	HANDWARMER KIT, DRIFT CUTTER KIT, FRONT WEIGHT KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	FRONT WEIGHT KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER



POSITION 1 - TRACK MODE

A traditional track position with the grip of a track for normal operation.

POSITION 2 - WHEEL MODE

Effortlessly raise the rear wheel to make the machine function like a wheel-driven model.

POSITION 3 - DIG-IN MODE

Shift the rear wheel down to pitch the auger housing and dig into hard-packed snow.

Registered trademark and ™ trademark of AriensCo. Kawasaki®, Kohler® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2022 AriensCo. All rights reserved.

VISIT [ARIENS.EU](https://www.ariens.eu) FOR DETAILS

AN **ARIENS|CO** BRAND