

	Contains	m ²	weight
1 pack Nordic Universal	4 planks	2,24m ²	21,0 kg
1 pallet Nordic Universal	39 packs	87,33 m ²	855,8 kg

Product specifications

Dimensions	2413 x 232 mm
Total thickness	10,2 mm
Bevels	4 micro
Loc System	NordLoc
Level of use according to European standard EN10874	23 heavy domestic use
	34 heavy commercial use
Residential warranty	lifetime
Commercial warranty	10 years

Warranty conditions on www.berryalloc.com.

Composition

Surface layer	AC6, High pressure laminate, impregnated with melamine and phenol resin
Substrate	Water resistant High Density Fiberboard (+950 kg/m ³)
Backing	Engineered balancing foil

Test results

	Norm	Results
Abrasion resistance	EN 13329	AC6 (IP 8500)
Impact resistance	EN 13329	small ball : ≥ 15 N - big ball ≥ 1600 mm)
Thickness swelling	ISO 24336	7 % (requirement 8 %)
Water resistance	ISO 4760	lifetime (according to warranty conditions)
Fire resistance	EN 13501-1	Bfl -S1
Formaldehyde emission	EN 717-1	E1
Slip resistance	EN 13893	DS
Density	EN 323	950 kg/m ³
Resistance to staining	EN 438.2.26	5 (groups 1+2) ; 4 (group 3)
Effect of a furniture leg	EN 424	no damage (foot type 0)
Effect of a castor chair	EN 425	No damage or visible change in appearance at 25.000 rev. with hard wheels (type H)
Thermal resistance without integrated underlay	ISO 8302 (EN 12664 / EN12667)	0,072 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com .

