

TEKNISK DATABLAD

AQUARELLE VÅTROMSGULV 2 m

TopClean PUR-forsterket
(Kolleksjon 2016 - 2017)

September 2016

Gulvtype

EN 649

Vinylgulv

Bruksklasse

EN 685



23



31

Klasse



EN 428

Total tykkelse

1,500 mm



EN 429

Slitesjikt

0,35 mm



EN 426

Dimensjon

18- 25 m
2m



EN 430

Total vekt

2 400 kg/m²



EN 660-2

Slitasjegruppe

T



EN 433

Inntrykks-
merker

≤ 0,10 mm

Annen informasjon



ISO 105/B02

Lysekthet

≥ 6



EN 1815

Statisk oppladning

≤ 2 kV



EN 12524

Varmemotstand 0,02 m²/kW



EN 13501-1

Brannklasse

Bfl-s1

Sklihemming



EN 13893

DIN 51130

≥ 0,30 µ
R9



EN 13553

Vanntetthet

Godkjent



Aquarelle Floor 3 m

0131-0005-DoP-2013-07
www.tarkett.se

Made by: Tarkett GDLSA.
Lentzweiler - LUXEMBURG



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.